

G 25/2.00A/F BL

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Product image



For protection against overcurrent, we offer cartridge fuse with dimensions 5x25 mm in sizes from 250 mA to 6.3 A.

General ordering data

Version	Miniature fuse, quick-acting, 2 A, G-Si. 5 x 25
Order No.	0192700000
Type	G 25/2.00A/F BL
GTIN (EAN)	4008 190176402
Qty.	10 items

Technical data

Approvals

ROHS	Conform
------	---------

Dimensions and weights

Height	25 mm	Height (inches)	0.9842 inch
Width	5 mm	Width (inches)	0.1968 inch
Net weight	1.4 g		

Temperatures

Ambient temperature	-5 °C...40 °C
---------------------	---------------

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

Material data

Colour	Light Grey
--------	------------

System specifications

Version	Fuse accessories
---------	------------------

Fuse cartridges

Optical function display	Yes	Cartridge fuse	G-Si. 5 x 25
Current	2 A	Version	Fuse accessories
Colour	Light Grey	Voltage drop	360 mV
Colour of the indicator	blue	Rated breaking capacity	1.5 kA
Melting integral	9.6 A²s	Characteristics	quick-acting
Power output (@ 1.5 In)	0.7 W		

Rating data

Rated voltage	250 V	Nominal current	2 A
---------------	-------	-----------------	-----

Classifications

ETIM 6.0	EC000035	ETIM 7.0	EC000035
ETIM 8.0	EC002704	ETIM 9.0	EC002704
ETIM 10.0	EC002704	ECLASS 9.0	27-14-20-01
ECLASS 9.1	27-14-20-01	ECLASS 10.0	27-14-20-01
ECLASS 11.0	27-14-20-01	ECLASS 12.0	27-14-20-01
ECLASS 13.0	27-14-20-01	ECLASS 14.0	27-14-20-01
ECLASS 15.0	27-14-20-01		