


## 100-ISO4-R16-RO: RIXC Ø16x2 ISO 6mm Red 100m



### Commercial information

The multilayer pipes come with a round or eccentric thermal insulating material. This material is made from extruded PE foam with a closed cell. The PE foam has a sturdy outer layer made from PE with a red or blue meshed vapour tight structure. This protects the foam against damage, so that the insulating properties of the product are not lost even during rough building work.

#### Basic unit dimensions

Height	28 mm
Length	1,000 mm
Width	28 mm
Net weight	0.131 kg

#### Certificates

ATG, QB (CSTBat), DVGW Wasser, ETA, ÖVGW Wasser, SITAC, KOMO, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, Bureau Veritas, RISE, SINTEF, WRAS, AFNOR, PZH, STF, ACS, Aenor, WQA, EMI

#### Applications

Potable water, Heating, Cooling, Compressed air, Demi Water, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

Material inner layer	Plastic (expired)	Number of layers	5
Quality class inner layer	PE-Xc	Outer pipe diameter	16 Millimetre
Material intermediate layer	Aluminium	Wall thickness	2 Millimetre
Material outer layer	Plastic (expired)	Medium temperature (continuous)	- Degrees celsius 10 7 0
Quality class outer layer	PE-Xc	Max. medium temperature (momentarily)	95 Degrees celsius
Glass-fibre reinforced	✘	Max. operating pressure at 20 °C	10 Bar
Diffusion-proof	✓	Max. operating pressure at max. medium temperature	10 Bar
Nominal diameter	DN 12	Wall roughness	0.00 Millimetre 7
System specific	✓	Expansion coefficient	0.02 Millimetre per metre Kelvin 5
Flexible	✓	Min. bending radius	48 Millimetre
Suitable for surface mounting	✓	Min. bending radius without tools	48 Millimetre
Pipe colour	Red	Outer diameter mantle pipe	0 Millimetre
With mantle pipe	✘	Thickness of thermal insulation	6 Millimetre
With heating cable	✘	Lambda value	0.43 Watt per metre Kelvin
KOMO certified	✓	Outer diameter thermal insulation	28 Millimetre
With thermal insulation	✓	Outer width rectangular insulation	0 Millimetre
Shape of insulation	Round	Outer height rectangular insulation	0 Millimetre
Colour of thermal insulation	Red	Water content	0.11 Litre per metre 3
DVGW quality mark	✓		
SVGW certified	✘		
Capped	✘		
UV resistant	✘		
Halogen free	✓		
Hook-and-loop fastening	✘		
Certified according to SVGW for water	✘		
Certified according to SVGW for gas	✘		
DIN-CERTCO certificate	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✓		
Compliant with NF 545	✓		
KIWA certified	✘		
Gastec QA mark	✘		
KOMO certified	✓		
Type approval according to BBR/EKS	✘		