

**WQV 2.5/3****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image**

Screwable cross-connections are easy to mount and de-mount. Thanks to the big contact surface, even high currents can be transmitted with maximum contact reliability.

**General ordering data**

Version	Cross-connector (terminal), when screwed in, yellow, 32 A, Number of poles: 3, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7 mm
Order No.	<a href="#">1053760000</a>
Type	WQV 2.5/3
GTIN (EAN)	4008 190058999
Qty.	50 items

**WQV 2.5/3**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Technical data**

**Approvals**

ROHS Conform

**Dimensions and weights**

Depth	18 mm	Depth (inches)	0.7087 inch
Height	14.2 mm	Height (inches)	0.5591 inch
Width	7 mm	Width (inches)	0.2756 inch
Net weight	2.26 g		

**Temperatures**

Storage temperature	-25 °C...55 °C	Ambient temperature	-5 °C...40 °C
Continuous operating temp., min.	-60 °C	Continuous operating temp., max.	130 °C

**Environmental Product Compliance**

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

**Material data**

Basic material	PA 66	Colour	yellow
UL 94 flammability rating	V-0		

**System specifications**

Version For the terminals

**Additional technical data**

Type of fixing	when screwed in	Installation advice	Direct mounting
----------------	-----------------	---------------------	-----------------

**Cross-connector**

Number of cross-connected terminals	3	Type	Cross-connector
Tightening torque range for fixing screw	0.4...0.8 Nm	Rated current, 2-pole	32 A
Rated current, multi-pole	32 A		

**Dimensions**

Pitch in mm (P) 5.10 mm

**General**

Number of poles	3	Installation advice	Direct mounting
-----------------	---	---------------------	-----------------

**Rating data**

Nominal current 32 A

**Classifications**

ETIM 6.0	EC000489	ETIM 7.0	EC000489
ETIM 8.0	EC000489	ETIM 9.0	EC000489

### Technical data

ETIM 10.0	EC000489	ECLASS 9.0	27-14-11-40
ECLASS 9.1	27-14-11-40	ECLASS 10.0	27-14-11-40
ECLASS 11.0	27-14-11-40	ECLASS 12.0	27-14-11-40
ECLASS 13.0	27-25-03-03	ECLASS 14.0	27-25-03-03
ECLASS 15.0	27-25-03-03		