



108221 - Plastbelagt lærredstape

Description	Tapen består af en PE coated lærredstape med en gummibaseret klæber.
Product properties	All-round lærredstape med høj klæbekraft og med en god balance mellem styrke og overrivbarhed. Tapen er fleksibel og med god fugtbestandighed. Den har lav VOC emission.
Applications	Anvendes til generelle isolerings- og ventilationsopgaver og forsegling og lukning af plastikposer samt generel pakning og reparationsopgaver. Anvendes ligeledes til midlertidig strapping.
Storage and ageing	Opbevaring ved +20°C og 50% relativ fugtighed - og ikke i direkte sol.
Applying tips	Alle overflader skal være rengjorte og klar til montering. Afrensning foretages bedst med IPA (iso-propyl-alkohol) og en ren klud. Det anbefales at montere tapen over et fast underlag, og ved temperaturer der almindeligvis ikke er under +10 grader.

TECHNICAL DATA

Carrier	Cloth/PE coated	
Adhesive	Rubber natural	
Colour	Black, Silver	
Thickness Total	0,28 mm	11 Mils
Adhesion on stainless steel	19,2 N/25mm	4,39 Lbs/inch
Tensile strength length	105 N/25mm	24 Lbs/inch
Service temperature	Between 4 and 93 °C	Between 39,2 and 199 °F

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.

See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use.

Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.

Stokvis Tapes (UK) Ltd
Unit 8, Tring Industrial Estate
Icknield Way, Tring, Hertfordshire
tel +44 (0)14 42 82 17 00
fax +44 (0)14 42 82 17 22
www.stokvistapes.co.uk
info@stokvistapes.co.uk