

## 125501BL - Udendørs afdækningstape

Description	Denne tape består af svagt creppet papir med en vandbaseret akrylklæber.
Product properties	Den har en god klæbeevne på glatte overflader og er modstandsdygtighed overfor fugt og UV lys. Betinget af den påmonteret overflades beskaffenhed, kan den sidde monteret i op til 15 dage i udendørs applikationer. Tapen er fleksibel og nemt at kurve. Den er kompatibel med de fleste almindelige maling og laktyper. Den er nem at fjerne igen, uden at den efterlader klæberester. Kan rives over i hånden. Tapen bør ikke fjernes så længe malingen er våd.
Applications	Premium vandfast afdækningstape til både indendørs og udendørs applikationer. Velegnet til afdækning i bygning og industri. Kan bruges på bla. metal, aluminium, plastik og træ.
Storage and ageing	1 års holdbarhed ved opbevaring i original emballage og ved omkring +20°C - 50% relativ fugtighed - og ikke i direkte sol.
Applying tips	Alle overflader skal være rengjorte og klar til montering. Tapen skal påføres ved hjælp af tryk.

### TECHNICAL DATA

UV resistant	Yes	
Color	Blue	
Thickness carrier	0.11 mm	4.331 Mils
Thickness total	0.125 mm	4.921 Mils
Adhesion on SS	3 N/25mm	0.69 Lbs/inch
Tensile strength length	110 N/25mm	25.12 Lbs/inch
Elongation length	10 %	

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information. See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application. The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use. Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.