



1375055-2 | JACK,SL110,RJ45,CAT6,BLK
RJ45 Jack, Category 6, 8-position, unshielded, without dust cover, black

Body Features

110 Block Material	Polycarbonate
Inverted Jack Face	Yes

Configuration Features

Keyed	No
Number of Positions	8
Wiring Pattern	Universal

Contact Features

Contact Base Material	Beryllium copper
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Thickness	50.0 µin 1.3 µm

Dimensions

Conductor Outside Diameter	.057 in 1.45 mm
Solid Wire Range	.51 mm ² .65 mm ²
Stranded Wire Range	.14 mm ² .2 mm ²
Wire Range	22 AWG 24 AWG 26 AWG

Housing Features

Housing Color	Black
Housing Material	Polycarbonate

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Mechanical Attachment

Mounting Type	SL Series Faceplate
---------------	---------------------

Other

Comment	With strain relief.
---------	---------------------

Packaging Features

Packaging Method	Poly Bag
Packaging Quantity	1

1375055-2 | JACK,SL110,RJ45,CAT6,BLK

Product Availability

Region Asia | Australia/New Zealand | EMEA | Latin America | North America

Product Type Features

Product Type	Connector - Modular
Connector Style	Jack
Jack Type	RJ45
Applies To	Panel
Cable Type	Unshielded Twisted Pair
Connector Type	Connector Assembly
Dust Cover	Without
Performance Category	Cat 6
Shielded	No

Termination Features

Termination Method to Wire/Cable	Insulation Displacement Crimp (IDC)
Termination Style	SL Termination Tool

Regulatory Compliance/Certifications

Agency
RoHS 2011/65/EU

Classification
Compliant