

13PKW-160416-X: T-hun center Hvid 16x1/2"x16 inox



Kommerciel information

PVDF pressfittings i kombination med alupexrør, et fuldstændigt korrosionsfrit system. De syntetiske pressefittings er lavet af sprøjtetøbt PVDF (Polyvinylidenfluorid)*. PVDF tilbyder brugeren en unik kombination af egenskaber: Meget modstandsdygtig over for tryk og temperatur. Fremragende mekanisk styrke Ekstrem fleksibilitet: bøjning op til 10° er mulig. Perfekt egnet til drikkevand. Meget modstandsdygtig over for kemikalier og korrosion. Indstøbning er mulig uden ekstra beskyttelse.

Grundlæggende enhedsmål

Højde	34 mm
Længde	109 mm
Bredde	50 mm
Nettovægt	0,093 kg

Certifikater

QB (CSTBat), ATG, AFNOR, ACS, DVGW Wasser, Aenor, Sans 21003

Ansøgninger

Drikkevand, Varme, Køl, Trykluft, Demi Vand, Sanitære


Løsninger

Bygningsinstallationer, Industri, Laboratorier, Infra, Skibsbygning

Tekniske egenskaber

Material connection 1	Polyvinylidene fluoride (PVDF)	Angle	90 Degrees
Surface protection connection 1	Untreated	Outer pipe diameter connection 1	16 Millimetre
Surface treatment connection 1	Untreated	Wall thickness, connection 1	0,7 Millimetre
Material connection 2	Stainless steel	Outer pipe diameter connection 3	16 Millimetre
Surface protection connection 2	Untreated	Wall thickness, connection 3	0,7 Millimetre
Surface treatment connection 2	Untreated	Length of connection 1	54,5 Millimetre
Material connection 3	Polyvinylidene fluoride (PVDF)	Working length connection 1	27,5 Millimetre
Model	T-piece	Length of connection 2	39 Millimetre
Swept entry type (with inner radius)	✘	Working length connection 2	25 Millimetre
Reducing	✘	Length of connection 3	54,5 Millimetre
System specific	✓	Working length connection 3	27,5 Millimetre
Connection 1	Press sleeve	Wrench width	0 Millimetre
Nominal diameter connection 2	1/2 inch (15)	Max. operating pressure at 20 °C	16 Bar
Connection 2	Internal thread cylindrical BSPP-G (ISO 228-1)	Wrench width union nut	0 Millimetre
Connection 3	Press sleeve	Medium temperature (continuous)	-10 70 Degrees celsius
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)	Standard Dimension Ratio (SDR)	0
Main colour fitting	White		
High tensile strength	✘		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
With drain valve	✘		
With de-aerator	✘		
With thermal insulation	✘		
With buffer stud	✓		
Capped	✘		
FM quality mark	✘		
LPCB quality mark	✘		
ULC quality mark	✘		
UL quality mark	✘		
DIN-CERTCO certificate	✘		
VdS quality mark	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✘		
KIWA certified	✘		
Gastec QA mark	✘		
KOMO certified	✘		
Type approval according to BBR/EKS	✘		

Relaterede produkter

Produktkode	GTIN	Beskrivelse	Billede
BE16	05414764454552	Henco Jaws (universal) BE/TH-Profile 16x2	
PK-TOOL04	05414764454552	Henco Wrench for PK/SK fittings with threading 1/2"	
PRESSCHECK1432	05414764454552	Henco Tool to control the accuracy of a pressing Ø14-32	