



1711160-1 | ASSY AMP-TWIST-6S SLJACK

AMP-TWIST 6S SL Jack, Category 6, shielded, 8-position, with dust cover

Body Features

110 Block Material	Polycarbonate
Cover Color	Transparent
Cover Material	Polycarbonate
Shield Material	Stainless steel

Configuration Features

Keyed	No
Number of Positions	8
Wiring Pattern	Universal

Contact Features

Contact Base Material	Beryllium copper
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Thickness	50.0 μin 1.3 μm

Dimensions

Cable Diameter (Max)	9.0 mm 0.4 in
Conductor Outside Diameter	.0629 in 1.6 mm
PCB Thickness (Recommended)	1.6 mm 0.1 in
Solid Wire Range	24 – 22 AWG
Stranded Wire Range	26 – 24 AWG

Housing Features

Housing Color	Gray
Housing Material	Zamak 5

Other

Comment	Rear Exit
---------	-----------

Packaging Features

Packaging Method	Box Tray/Box
Packaging Quantity	12

Product Availability

Region	Australia/New Zealand EMEA
--------	------------------------------

Product Type Features

Product Type	Connector - Modular
Connector Style	Jack
Jack Type	RJ45
Applies To	Panel
Connector Type	Connector Assembly
Dust Cover	With
Performance Category	Cat 6
Shielded	Yes

Termination Features

Termination Method to Wire/Cable	Insulation Displacement Crimp (IDC)
Termination Style	SL Termination Tool

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

Classification

Compliant