



**Switch for card 6 (2)A
250V~ with fast
connection graphite
Simon 24 Harmonie**

Ref.: **2411526-038**

BASIC INFORMATION

Finish	Graphite
Indicator function	No
Consumption indicator	1 mA
No. of possible elements	1 element
Compatibility	Simon 24 Harmonie frames
Packaging contents	Mechanism
Remarks	Recommended installation by linking the item to a relay. Otherwise, the switch's maximum current is 6A (inductive 2A).
Series	Simon 24 Harmonie
Version	Single
Intensity	6(2) A
Voltage	250V~
Monoblock	No
Type of terminal connection	Faston
Type of mechanism	Key card

Technical information

Cable section admitted	From 0.5 mm
IP rating	20
IK Classification	Sí
Manufacturing material	Halogen-free thermoplastic
Type of product	Standard
Market available	CE, except for Spain, UK, Poland, Portugal, Andorra and Russia

Installation and maintenance

Installation type	Flush-mounted or surface-mounted
Installable in flush mount junction box	Universal
Operating temperature range	5 to 40 °C
Storage temperature range	-25 to 50 °C



www.simonelectric.com



SIMON, S.A.U.

Diputación, 390-392
08013 Barcelona (Spain)
Tel.: +34 93 547 81 81