



**2-way switch 10AX
250V~ with built-in pilot
light and fast terminal
connectionwhite Simon
24 Harmonie**

Ref.: **2420204-030**

BASIC INFORMATION

Finish	White
Indicator function	Sí
Consumption indicator	0.5 mA
No. of possible elements	1 element
Claw	Push&Go
Compatibility	Simon 24 Harmonie frames
Packaging contents	Mechanism
Series	Simon 24 Harmonie
Version	Single
Intensity	10A
Voltage	250V~
Type of terminal connection	Fast
Type of mechanism	Rocker

Technical information

Cable section admitted	From 1.5 to 2.5 mm
Cable stripping necessary	14 mm
IP rating	20
IK Classification	Sí
Manufacturing material	Metal components with halogen-free thermoplastic insulator
Type of product	Standard
Market available	CE, except for Spain, UK, Poland, Portugal, Andorra and Russia

Regulations

Regulations	NM 06.6.001-2015
-------------	------------------

Installation and maintenance

Installation type	Flush-mounted or surface-mounted
Installable in flush mount junction box	Universal
Operating temperature range	5 to 40 °C
Storage temperature range	-25 to 50 °C



www.simonelectric.com



SIMON, S.A.U.

Diputación, 390-392
08013 Barcelona (Spain)
Tel.: +34 93 547 81 81