



**Switch for blinds 10A
250V~ with 3 positions
with fast terminal
connection white Simon
24 Harmonie**

Ref.: **2420333-030**

BASIC INFORMATION

| | |
|-----------------------------|--------------------------|
| Finish | White |
| Indicator function | No |
| No. of possible elements | 1 element |
| Claw | Push&Go |
| Compatibility | Simon 24 Harmonie frames |
| Packaging contents | Mechanism |
| Series | Simon 24 Harmonie |
| Version | Single |
| Intensity | 10A |
| Voltage | 250V~ |
| Type of terminal connection | Fast |
| Type of mechanism | Rocker |
| No. of functional positions | 3 |

Technical information

| | |
|---------------------------|--|
| Cable section admitted | From 1.5 to 2.5 mm |
| Cable stripping necessary | 11 mm |
| IP rating | 20 |
| IK Classification | Sí |
| Manufacturing material | Metal components with halogen-free thermoplastic insulator |
| Type of product | Standard |
| Market available | CE, except for Spain, UK, Poland, Portugal, Andorra and Russia |

Regulations

| | |
|-------------|------------------|
| Regulations | NM 06.6.001-2015 |
|-------------|------------------|

Installation and maintenance

| | |
|---|----------------------------------|
| Installation type | Flush-mounted or surface-mounted |
| Installable in flush mount junction box | Universal |
| Operating temperature range | 5 to 40 °C |
| Storage temperature range | -25 to 50 °C |



www.simonelectric.com



SIMON, S.A.U.

Diputación, 390-392
08013 Barcelona (Spain)
Tel.: +34 93 547 81 81