

TF-K50

Torque wrench TORCOFIX TF-K

Code	ETIM
3288242	EC002132
EAN	UNSPSC
4010886965573	27-11-17-15
Country of origin	
Germany	
Customs tariff number	
82041100	



Article description

- Use:
- Controlled screw tightening in the range of 10 - 50 Nm / 7,5 - 37 lbf-ft
- Adjustable, releasing and sturdy tubular torque wrench with integrated ratchet and with square drive for industry and the trades
- Features:
- Classified as per DIN EN ISO 6789-2:2017 Type II Class A; adjusted to a maximum permissible +/-3 % deviation and thus with a greater precision than the standard-stipulated +/-4 %
- Incl. traceable test certificate (DIN EN ISO 6789-2:2017)
- For controlled right- and left-hand tightening (square socket for direction change)
- 3/8" mushroom head socket square with ball lock
- Robust, matt powder-coated tubular steel construction, with galvanized ratchet and high-quality plastic parts
- New ergonomic handle, shaped according to the natural grip position of the hand
- clearly recognisable and tactile hand centring aid and calibration aid in the middle of the handle
- Double scale Nm / lbf-ft and vernier are protected from abrasion and contamination by an enlarged viewing window
- With vernier scale for Nm main scale for setting intermediate scale values; lbf-ft setting only via main scale
- Vertical alignment of the scale, torque adjustment therefore suitable for left and right handers
- Scale line positioned directly above the scale prevents reading errors (parallax errors)
- Unit labeling integrated in the scale frame and also protected by viewing windows
- The precise release mechanism generates a distinct tactile and audible release signal when the set torque value is reached
- incl. roll away protection, prevents rolling away when the tool is put down

Article information

Drive connector square (male)	3/8"	Number of teeth	36
Contents (Qty of pieces)	1	Width of head l [mm]	35,0 mm
Total length [mm]	303 mm	Distance housing - square drive	17,5 mm
Torque (min.) [N·m]	10 Nm	Drive type/drive	Mushroom head
Torque (max.) [N·m]	50 Nm	vernier Nm	0,25 Nm
Torque (min.) [lbf-ft]	7,5 lbf-ft	Standard	DIN 3120 - A 10 ISO 1174
Torque (max.) [lbf-ft]	37 lbf-ft	Calibration length	230,5 mm
Torque range (min./max.) [N·m]	10 Nm - 50 Nm	Net weight [kg]	0,42 kg
Torque range (min./max.) [lbf-ft]	7,5 lbf-ft - 37 lbf-ft	Graduation [lbf-ft]	25 lbf-ft
Total width [mm]	39 mm	Storage/Content	Plastic box
Total height [mm]	39,8 mm	Trigger mechanism	Short path triggering
Material	Tubular steel construction, top-grade plastic parts	Precision +/-	+/- 3 %
Drive connector square (male)	10 mm	Direction of tightening	Left and right
Graduation	2,5	Fixed setting	no
Return angle	10°	Test certificate	DIN EN ISO 6789-2:2017
Head height l [mm]	25,3 mm	Graduation [n·m]	2,5 Nm