



jalas[®] M-SPORT 3468A LIGHT SPORT

EN ISO 20345:2022 S3L, FO



[Learn more](#)

A low cut, sporty and lightweight safety shoe with highest (S3) protection and excellent comfort. The split leather and functional textile upper supports and protects your feet in comfort for days on the job. An oil-resistant PU outer sole provides excellent grip in the slip, and JALAS[®] aluminium toe cap, plasma-treated textile puncture protection and double impact protection zones in Ergothan[®] mean safer feet all round.

CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Good shock absorption

FUNCTIONS

- ProNose toe reinforcement
- Oil-resistant outsole
- Anti-static properties
- Water repellent
- Low weight
- Polstered shaft edge
- Ventilating insole
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)



PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, environments with risk for outsole penetration

SPECIFICATION

TYPE Safety footwear, Low shoes

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

COLLECTION M-Sport

UPPER MATERIAL Split leather, Textile

PRONOSE MATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, polyamide

INSOLE FX2 Classic

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Shock absorption zone in Ergothan

OUTSOLE MATERIAL PU outsole

FASTENING Laces

SHOELACES LENGTH 100 cm

COLOUR Black, Orange

NET WEIGHT, (SIZE 42) 1.15 kg

COMPLIANCE



TP TC 019:2011

EN ISO 20345:2022
S3L, FO



ÖNORM Z 1259



DGVU 112-191

FEATURES



Anti-static properties



Ergothan Shock Absorption System



ESD



Aluminium toecap



Oil-resistant outsole



ProNose toe reinforcement



Nail protection in plasma-treated composite (PTC) textile



Water repellent

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	3468A-36	6408487413964
37	4	5	6	3468A-37	6408487413971
38	5	5½	6½	3468A-38	6408487413988
39	6	6½	7½	3468A-39	6408487413995
40	6½	7½	8½	3468A-40	6408487414008
41	7	8	9	3468A-41	6408487414015
42	8	9	10	3468A-42	6408487414022
43	9	9½	11	3468A-43	6408487414039
44	10	10½	11½	3468A-44	6408487414046
45	10½	11	12½	3468A-45	6408487414053
46	11	12	13	3468A-46	6408487414060
47	12	13	14	3468A-47	6408487414077

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com