


# TECHNICAL DATASHEET

# 506U040405

Rev.00



## FEATURES:

- New technical features and design
- Panoramic wrapping lens available with AF+ and AS+ coatings
- Temples regulation in length and inclination
- Soft terminal tips to eliminate local pressure
- Optimal comfort and fit thanks to the soft adjustable nosepad
- New range of colours

## FRAME FEATURES:

Frame Typology	<b>Spectacle</b>
PPE field of view	<b>&gt;40</b>
Temple adjustment	<b>Inclination and Length</b>
Weight (g)	<b>25</b>
Size	<b>136 119-126</b>
Material Features	<b>Latex free</b>

## FEATURES OCULARS/LENSES:

Ocular/Flip-up Material	<b>Polycarbonate</b>
Colour	<b>Green</b>
Technical Treatment	<b>Antiscratch</b>
Aesthetic Treatment	-
Thickness	<b>2.3</b>
Curvature	<b>Base 9</b>
Optical Class	<b>1</b>
UV Protection	<b>400</b>
Spare Parts	-
VLT% (+/-5%)	<b>17,7</b>

## MARKING DATA:

Standard References	<b>EN166 EN170 EN172</b>
Frame Marking	<b>Mod.506U U EN166 FT CE</b>
Ocular/Flip-up Marking	<b>2C-3/5-3.1 U 1 FT CE</b>

## APPLICATION FIELDS

Protection against high-speed particles - low energy (F); Protection against high-speed particles at extreme temperatures (T)

Notes

