

TECHNICAL DATASHEET

5X3033300

Rev.00

U+DC



FEATURES:

- Exclusive UDC coating
- Lens with FLD (Floating Lens Design) technology
- Frame engineered to cushion the contact points on the face
- Extended 9 base wraparound lens, provides extra coverage around the eyes
- Ventilation system
- The spectacle fits the face without adjustments

FRAME FEATURES:

Frame Typology	Spectacle
PPE field of view	>40°
Temple adjustment	-
Weight (g)	31
Size	142 122
Material Features	Anallergic

FEATURES OCULARS/LENSES:

Ocular/Flip-up Material	Polycarbonate
Colour	Clear
Technical Treatment	U+DC
Aesthetic Treatment	-
Thickness	2.2
Curvature	Base 9 Spheric
Optical Class	1
UV Protection	380 nm
Spare parts	-
VLT% (+/-5%)	91,2

MARKING DATA:

Standard References	EN166 EN170
Frame Marking	Mod.5X3 U EN166 FT CE U EN 175 FT CE
Ocular/Flip-up Marking	2C-1.2 U 1 FT K N CE

APPLICATION FIELDS

Protection against high-speed particles 45 m/s - low energy (F); Protection against high-speed particles at extreme temperatures (T); Resistance to fogging of oculars (N); Resistance to surface damage by fine particles (K)

Notes

