

TECHNICAL DATASHEET

5X9030000

Rev.00



FEATURES:

- Univet project, innovative design
- Integrated side shields with ventilation system
- Adjustable temples with SoftPad technology
- Clear lenses available in different materials
- Additional flip with protective filters for special applications

FRAME FEATURES:

Frame Typology	Spectacle
PPE field of view	>40
Temple adjustment	Inclination and Length
Weight (g)	35
Size	58 □ 16 X 110 - 120
Material Features	Latex free

FEATURES OCULARS/LENSES:

Ocular/Flip-up Material	Polycarbonate
Colour	Clear
Technical Treatment	Antifog PLUS Antiscratch PLUS
Aesthetic Treatment	-
Thickness	2
Curvature	Base 6
Optical Class	1
UV Protection	380
Spare Parts	-
VLT% (+/-5%)	91,2

MARKING DATA:

Standard References	EN166 EN170
Frame Marking	Mod.5X9 U EN166 FT CE L
Ocular/Flip-up Marking	2C-1.2 U 1 FT K N CE

APPLICATION FIELDS

Protection against high-speed particles - low energy (F); Protection against high-speed particles at extreme temperatures (T); Resistance to fogging of oculars (N); Resistance to surface damage by fine particles (K)

Notes

