

### Product Datasheet uvex 2 6522.1-4 S3 HI HRO SRC



**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth**

#### Product information

- Sporty, multifunctional safety shoes
- Extremely light and flexible
- The latest generation of 100% metal-free uvex xenova® toe cap. Compact design, anatomical shape, good side and ankle twist stability, no thermal conductivity and antimagnetic properties
- Metal-free, penetration-resistance insole in accordance with the latest standard, which does not impact shoe flexibility
- Made with new high-performance technology for exceptional wearer comfort
- uvex climazone technology for optimum comfort
- Water-repellent, breathable and extremely soft leather upper
- Distance mesh lining provides optimum breathability
- Individually adjustable due to elastic laces with quick-lock mechanism; normal laces also provided
- Virtually seam-free construction to eliminate pressure points
- Removable comfort insole, antistatic, with moisture control system and additional shock absorption in the heel and at the front of the foot
- Soft, padded collar and padded tongue
- Injection-moulded polyurethane scuffcap to protect upper leather on toe cap and significantly extend resistance time
- Meets ESD requirements: resistance to ground < 35 megaohm

#### Outsole

- Lightweight two-layer insole with excellent shock absorption characteristics and outstanding slip

	<p>resistance</p> <ul style="list-style-type: none"> <li>• Multilayer shock absorption system comprising PU mid sole, highly slip resistance rubber outsole from Vibram and comfortable insole, shock absorption in the front and heel: all this protects the musculoskeletal system, even over long periods of time</li> <li>• Optimised ankle protection to ensure safety when working on ladders</li> <li>• Rugged, self-cleaning sole ridges ensures maximum grip for demanding applications on uneven or dirty floors (SRC labelling).</li> <li>• withstands brief exposure to heat of approx. +300°C</li> </ul>																				
<b>Technical data</b>	<table> <tr> <td>Art.-no.</td> <td>6522.1</td> <td>.2</td> <td>.3</td> <td>.4</td> </tr> <tr> <td>Fitting</td> <td>10</td> <td>11</td> <td>12</td> <td>14</td> </tr> <tr> <td>Standard</td> <td colspan="4">EN ISO 20345:2011 S3 HI HRO SRC</td> </tr> <tr> <td>Size</td> <td colspan="4">35 – 52</td> </tr> </table>	Art.-no.	6522.1	.2	.3	.4	Fitting	10	11	12	14	Standard	EN ISO 20345:2011 S3 HI HRO SRC				Size	35 – 52			
Art.-no.	6522.1	.2	.3	.4																	
Fitting	10	11	12	14																	
Standard	EN ISO 20345:2011 S3 HI HRO SRC																				
Size	35 – 52																				
<b>Accessories</b>	<p><i>uvex 1 comfortable climatic insole</i> (article no.: 9534.7-9 + .0)</p> <ul style="list-style-type: none"> <li>• Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones</li> <li>• Ultra breathable and moisture-absorbing materials</li> <li>• Shock absorption zones that assist natural movement</li> <li>• Non-irritating, comfortable surface structure</li> </ul> <p><i>Laces</i></p> <ul style="list-style-type: none"> <li>• Black (article no.: 9599.9 11)</li> <li>• Elastic laces (article no.: 9591.100)</li> </ul>																				