

Product Datasheet uvex 1 sport 6592.1-4 S1 P SRC

**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth**

| | |
|----------------------------|--|
| Product information | <ul style="list-style-type: none">• Modern, ultralightweight and flexible safety shoe• 100 % metal-free uvex xenova® toe cap – compact design, anatomical shape, good lateral stability, no thermal conductivity• Penetration-resistant, non-metallic midsole in accordance with the latest safety standards, does not restrict flexibility of the shoe• Outstanding wearer comfort results from a newly developed last and climate-optimised, breathable materials• uvex climazone technology for optimum comfort• Virtually seam-free construction made from high-tech materials to eliminate pressure points• Suitable for people allergic to chrome as it's made from synthetic materials• Removeable anti-static comfortable insole, with a moisture transport system and additional shock absorption around the heel and forefoot• Soft padding on collar and tongue• Sizes 35 – 40 have been produced using a women's last• Meets the ESD specification with leakage resistance less than 35 megaohms |
| Outsole | <ul style="list-style-type: none">• Ergonomically designed outsole comprising dual-density polyurethane with excellent slip resistant• All sole materials are free of silicones, plasticisers and other paint wetting impairment substances |

| | | | | | | | | | | | | | | | | | | | | | |
|-----------------------|---|----------|--------|----|----|----|---------|----|----|----|----|----------|----------------------------|--|--|--|------|---------|--|--|--|
| | <ul style="list-style-type: none"> • Withstands brief exposure to heat of approx. +120°C | | | | | | | | | | | | | | | | | | | | |
| Technical Data | <table> <tr> <td>Art.-no.</td> <td>6592.1</td> <td>.2</td> <td>.3</td> <td>.4</td> </tr> <tr> <td>Fitting</td> <td>10</td> <td>11</td> <td>12</td> <td>14</td> </tr> <tr> <td>Standard</td> <td colspan="4">EN ISO 20345:2011 S1 P SRC</td> </tr> <tr> <td>Size</td> <td colspan="4">35 – 52</td> </tr> </table> | Art.-no. | 6592.1 | .2 | .3 | .4 | Fitting | 10 | 11 | 12 | 14 | Standard | EN ISO 20345:2011 S1 P SRC | | | | Size | 35 – 52 | | | |
| Art.-no. | 6592.1 | .2 | .3 | .4 | | | | | | | | | | | | | | | | | |
| Fitting | 10 | 11 | 12 | 14 | | | | | | | | | | | | | | | | | |
| Standard | EN ISO 20345:2011 S1 P SRC | | | | | | | | | | | | | | | | | | | | |
| Size | 35 – 52 | | | | | | | | | | | | | | | | | | | | |
| Accessories | <p><i>removeable uvex 1 sport climatic insole</i> (article no.: 9579.7/.8/.9/.0)</p> <ul style="list-style-type: none"> • Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones • Ultra-breathable and moisture-absorbing materials • Shock absorption zones that assist natural movement • Non-irritating, comfortable surface structure <p><i>Laces</i></p> <ul style="list-style-type: none"> • Black (article no.: 8446.0 10) | | | | | | | | | | | | | | | | | | | | |