



TEGERA® INFINITY 8814



[Learn more](#)

GREAT FIT, PALM DIPPED, CUT F GLOVE

Dexterous cut resistant glove with highest cut level F and touchscreen function, suitable for all-round work. 13 gg knitted with CRF® cut resistant technology. Palm dipped with super soft nitrile foam that provides excellent grip in dry and slightly moist environments. Reinforced thumb crotch for improved longevity. Breathable materials for all day comfort. Protection against contact heat up to 100°C/212°F. Wide range of sizes means a perfectly fitting glove for everyone. Skin friendly with Derma-test and Oeko-Tex certificate.

CHARACTERISTICS

- Highest level of protection
- Good fingertip sensitivity
- Good grip
- Flexible
- Durable
- Comfortable

FUNCTIONS

- Withstands contact heat up to 100°C
- For touchscreen
- Approved for handling foodstuffs
- Reinforcement between index finger and thumb



PREVENTS RISK OF

Cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, dry environments, moist environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Building and construction, sheet-metal work, engineering, metalwork, glass industry work, repair work

PRIMARY INDUSTRIES OF USE

Glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, building and construction

TYPE OF WORK

Heavy weight

SPECIFICATION

TYPE Cut resistant gloves, Heat protection gloves

CATEGORY Cat. II

COLLECTION Infinity

LINING MATERIAL 13 gg, Basalt fibre thread, CRF[®] Technology, HPPE, Polyester, Spandex, Stainless steel fibre yarn

LENGTH 220-270 mm

DEXTERITY 5

GRIP DESIGN Foam grip pattern

COLOUR Black

PAIRS PER: BUNDLE/CARTON 6/120

DISPLAY TYPE Bulk pack

DIPPING Palm-dipped

DIPPING MATERIAL Nitrile foam, Waterbased PU

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

CUT RESISTANCE (EN ISO 13997) Cut resistance level F

CUT RESISTANCE (EN ISO 13997) TDM: 41.2N


INNER MATERIAL SPECIFICATION HPPE (High performance polyethylene), Polyester, Stainless steel fibre yarn, Basalt fibre thread, Elastane

OUTER MATERIAL SPECIFICATION Nitrile


COMPLIANCE



TP TC 019:2011




EN ISO 21420:2020



Contact heat rating valid for palm area only

FEATURES



SIZE		ARTICLE NUMBER	EAN
5	XXS	8814-5	7340118409177
6	XS	8814-6	7340118328683
7	S	8814-7	7340118324753
8	M	8814-8	7340118324760
9	L	8814-9	7340118324777
10	XL	8814-10	7340118324739
11	XXL	8814-11	7340118324746

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com