



## H1,5/14D SW



- supplied loose in poly-bag
- Weidmüller colour code
- DIN colour code

### General ordering data

|            |  |
|------------|--|
| Version    | Wire-end ferrule, Standard, 10 mm, 8 mm, black |
| Order No.  | <a href="#">9019120000</a>                     |
| Type       | H1,5/14D SW                                    |
| GTIN (EAN) | 4008190153793                                  |
| Qty.       | 500 items                                      |
| Packaging  | loose  |

Technical data

Approvals

Approvals



|                         |                            |
|-------------------------|----------------------------|
| ROHS                    | Conform                    |
| UL File Number Search   | <a href="#">UL Website</a> |
| Certificate no. (cULus) | E499744                    |

Dimensions and weights

|            |        |
|------------|--------|
| Net weight | 0.11 g |
|------------|--------|

Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

Technical data

|                        |   |         |          |
|------------------------|---|---------|----------|
| Description of article | Wire end ferrule with plastic collar, black | Version | Standard |
|------------------------|---|---------|----------|

Wire-end ferrules

|                               |          |   |                     |
|-------------------------------|----------|---|---------------------|
| Contact surface diameter (D1) | 1.7 mm   | Contact surface length (L2)             | 8 mm                |
| Collar diameter (D2)          | 3.5 mm   | Plastic collar thickness (S2)           | 0.25 mm             |
| L1 in mm                      | 14.00 mm | Wire connection cross section AWG, max. | AWG 16              |
| Metal sleeve thickness (S1)   | 0.15 mm  | Military designation                    | T 20A 012 A         |
| Stripping length              | 10 mm    | Conductor cross-section                 | 1.5 mm <sup>2</sup> |
| Colour code                   | DIN      |   |                     |

Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ETIM 8.0    | EC000005    | ETIM 9.0    | EC000005    |
| ETIM 10.0   | EC000005    | ECLASS 9.0  | 27-40-02-01 |
| ECLASS 9.1  | 27-40-02-01 | ECLASS 10.0 | 27-40-02-01 |
| ECLASS 11.0 | 27-40-02-01 | ECLASS 12.0 | 27-40-02-01 |
| ECLASS 13.0 | 27-40-02-01 | ECLASS 14.0 | 27-40-02-01 |
| ECLASS 15.0 | 27-40-02-01 |             |             |

Drawing

