


# PHILIPS

## MY CREATION

# Essential Series

Configuration code: BR-M-P-19S-940-DIA-OC-WH401-T102-WH-N-N-N



Size	Medium
Mounting	Pendant (P)
Lumen package	1900 Lumen
Luminous Flux (lumen)	1889.68
Luminous flux tolerance (Initial performance, IEC compliant)	+/- 10%
Power consumption (W)	15.4
Power consumption tolerance (Initial performance, IEC compliant)	+/- 10%
Luminous Efficacy (lm/W)	122.7
CCT	4000K, Ra 90+
Optics	MXO OC (UGR19)
Driver	For DALI Interact wired (DIA) system without sensor, through wiring
Emergencylighting	No integrated emergency lighting
Cable type	None
Mounting color	White Canopy
Texture	T102 Layered Fine
Shade/Trim color	WH401 Satin White (9003)
Ceiling size	Not applicable
Input Voltage	220-240 VAC
Frequency	50-60 Hz
Power Factor	> 0.90
Lifetime (hours)	100,000 hours for L80 @ T ambient 25 degrees
Protection Class	IP20 / IK04 ELECTRICAL CLASS II
Ambient Range	+10°C to +35°C
Certifications	CE, RoHS
Glow Wire Test	650°C

# PHILIPS

## MYCREATION

Warranty

5 years

Region

EU

Start configuration

