


# Essential Series

Configuration code:



Size	Large
Mounting	Pendant (P)
Lumen package	4600 Lumen
Luminous Flux (lumen)	4600
Luminous flux tolerance (Initial performance, IEC compliant)	+/- 10%
Power consumption (W)	34.5
Power consumption tolerance (Initial performance, IEC compliant)	+/- 10%
Luminous Efficacy (lm/W)	133.3
CCT	4000K, Ra 90+
Optics	MXO OC (UGR19)
Driver	For DALI Interact wired (DIA) system without sensor, through wiring
Emergencylighting	No integrated emergency lighting
Cable type	None
Mounting color	Black Canopy
Texture	T102 Layered Fine
Shade/Trim color	BK402 Satin Black (9004)
Ceiling size	Not applicable
Region	EU
Input Voltage	220-240 VAC
Frequency	50-60 Hz
Power Factor	> 0.90
Lifetime (hours)	100,000 hours for L80 @ T ambient 25 degrees
Protection Class	IP20 / IK04 ELECTRICAL CLASS II
Ambient Range	+10°C to +35°C
Certifications	CE, RoHS

# Signify myCreation

Glow Wire Test	650°C
Warranty	5 years
Region	EU
Configuration code (Internal use only)	TC BR L P 46S 940 DIA OC N BK402 T102 BK N

[Start configuration](#)

