

**Product Datasheet model sportstyle 9193 064**

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth

**Product  
characteristics**

- extremely light safety spectacle with a sporty design
- optimal vision thanks to the shape of the uvex lens, with scratch-resistant coating on the outside and anti-fog coating on the inside
- soft, adjustable nose piece and soft, non-slip ear pieces (uvex duo component technology) ensure a secure, pressure-free fit
- with CBR 65-Lens Technology:
  - C**ontrast (contrast-enhancing)
  - B**lue (reduction of blue light)
  - R**elax (relaxed view)
  - 65** (65% transmission)

## Technical details

### Frame

Material  
Features  
Colour

Material  
Colour

Manufacturer's ID  
code  
Applicable EN norm  
Impact resistance  
Resistance to high  
speed particles at  
extremes of  
temperat.  
Conformity symbol

### Front piece

PC-PBT / TPE  
individually adjustable nose pad  
white

### Temples

PC-PBT / TPE  
white, black

### Marking

W  
  
166  
F (45 m/s)  
T  
  
CE

|                                                             |                                                          |
|-------------------------------------------------------------|----------------------------------------------------------|
| <b>Lens</b>                                                 |                                                          |
| Material                                                    | PC                                                       |
| Thickness                                                   | 2,1 mm                                                   |
| Coating                                                     | uvex supravision extreme                                 |
| Colour                                                      | light brown (CBR 65)                                     |
| UV protection                                               | UV 400                                                   |
| <b>Marking</b>                                              |                                                          |
| Filter                                                      | 5-1,4 (DIN EN 172)                                       |
| Manufacturer's ID code                                      | W                                                        |
| Optical class                                               | 1                                                        |
| Impact resistance                                           | F (45 m/s)                                               |
| Resistance to high speed particles at extremes of temperat. | T                                                        |
| Surface resistance to fine particles                        | K                                                        |
| Antifog                                                     | N                                                        |
| Conformity symbol                                           | CE                                                       |
| <b>Miscellaneous</b>                                        |                                                          |
| Weight                                                      | 23 g                                                     |
| Packing                                                     | 5 spectacles per box<br>160 spectacles per cardboard box |
| Standards                                                   | DIN EN 166 + DIN EN 172                                  |
| PPE Category                                                | Category II                                              |