



## ■ jalas® EXALTER 9915

EN ISO 20345:2011 S1, P, SRC, HRO ASTM F2413-18 M/I/C SD 35 PR



[Learn more](#)

### LOW-CUT WITH VENTILATION AND LACES

This low-cut safety shoe has the features you need for most work situations, such as PTC-textile nail protection, toecap in aluminum and high-grip Vibram Nitrile rubber outsole. The midsole and JALAS FX3 Supreme multilayer insole together with the sock-like construction provide ultimate comfort. PORON® XRD™ shock-absorption prevents injuries to foot and back. The upper has net-covered ventilation holes to keep feet cool and prevent particles from entering the shoes.

#### CHARACTERISTICS

- Excellent shock absorption
- Excellent grip
- Perfect fit
- Extra comfortable
- Very breathable

#### FUNCTIONS

- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Ergonomically shaped
- Soft
- Specially designed details
- Breathable mesh
- Polstered shaft edge
- Ventilating insole
- Stabilizator
- Free from animal-derived materials



**PREVENTS RISK OF**

Toe injuries, nail penetration, antistatic

**PRIMARY ENVIRONMENTS OF USE**

Outdoors, indoors, environments with risk for outsole penetration, dry environments, clean environments, warm environments

**SPECIFICATION**

TYPE Safety footwear, Low shoes

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

COLLECTION Exalter

UPPER MATERIAL Microfiber, Textile

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester

INSOLE JALAS 8303 FX3 Supreme

INNERSOLE MATERIAL Textile, Soft EVA, Rigid EVA, Polyester-based conductive thread, Neo foam, Double shock absorption zones in Poron® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING Laces

SHOELACES LENGTH 100 cm

COLOUR Black, Green

NET WEIGHT, (SIZE 42) 1.27 kg

**COMPLIANCE**



TP TC 019:2011

EN ISO 20345:2011  
S1, P, SRC, HRO

ASTM F2413-18  
M/I/C  
SD 35 PR



ÖNORM Z 1259



DGVU 112-191

**FEATURES**



Anti-static properties



Ergothan Shock Absorption System



ESD



Aluminium toecap



Oil-resistant outsole



Heat-resistant outsole



Nail protection in plasma-treated composite (PTC) textile



Stabilizer

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
34	1½	2½	3½	9915-34	6408487513176
35	2	3½	4	9915-35	6408487513183
36	3	4	5	9915-36	6408487513190
37	4	5	6	9915-37	6408487513206
38	5	5½	6½	9915-38	6408487513213
39	6	6½	7½	9915-39	6408487513220
40	6½	7½	8½	9915-40	6408487513237
41	7	8	9	9915-41	6408487513244
42	8	9	10	9915-42	6408487513251
43	9	9½	11	9915-43	6408487513268
44	10	10½	11½	9915-44	6408487513275
45	10½	11	12½	9915-45	6408487513282
46	11	12	13	9915-46	6408487513299
47	12	13	14	9915-47	6408487513305

**ejendals**

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com