

BEOVIEW7 Lite-S-touchscreen IP monitor, iPlus & iPlusBUS

- 7" colour TFT LCD with capacitive touch screen
- UV stable ABS plastic body.
- Specialized electronics and Firmware for stable and robust 24/7 operation.
- User friendly and intuitive GUI.
- Full duplex handsfree audio communication. Fully compliant PoE power supply.
- IP and IPBus installation.
- Surface installation (60mm European electrical box)
- Dimensions: 181(W) x 118(H) x 17,5(D) mm



beoview

Beoview Intercom d.o.o.
11070 Belgrade, Serbia
www.beoview.com

Display	7 "capacitive HR touchscreen (800 x 480 pixels)
Format	16:9
Brightness	240 cd/m2 (typical)
Contrast	500:1 (typical)
Color depth	24 bit color, 16.7 million colors
Touch Mode	Capacitive touch
Connectors	Ethernet RJ45, 6 pin terminal block for inputs and external speaker for ring tone
Loudspeaker and microphone	2W, 4 ohm speaker, electret microphone
Temperature range	0°C - 60 °C
Humidity	90% at 60 °C
Dimensions (with euro box)	With euro mounting box: 181 x 118 x 17,5mm (W x H x D)
Weight	370g (monitor with mounting plate); 450g (total with packaging)
Mounting	Surface mounting with metal bracket (provided)
Power	5W fully active, 1W idle, 48VDC PoE (under voltage cutoff 36VDC)

- PoE powered (IEEE 802.3af) from switch (iPlus) or T-Switch (iPlus BUS).
- Hardware based AES256 encryption for all monitor call communication.
- RJ45 connector, floor bell connection, inputs for special FW version.
- Visitor snapshot memory with missed call.
- Red flashing LED for displaying missed call and messenger message.
- Spy function, including audio audio communication.
- Simple user friendly graphic user interface.
- Video source label display.
- IP relays control for additional security.
- Call forwarding for iOS and Android Apps using IPGateway2 device or optional WIFI module.

We reserve the right to introduce modifications without notice.