

**Floorstanding WC combination with cistern
with fixing holes for floor fixation
82795.4**



TECHNICAL DATA

Order no.	82795.4
Certified to	EN 997
Specification	Washdown for 4,5/3-l-flush, Charge 737 2 fixing holes with cistern flushing mechanism, water condensation insulation, Dual-Flush (4,5/3-l-flush), water inlet bottom right 1/2" brass
Outlet	vertical
Weight	29,7 kg
Accessories excl.	Seat, order no. 89115.3 Seat and cover, order no. 89095.0 Seat and cover with automatic lowering system, order no. 89095.1
Mounting acc. incl.	Fastening kit, order no. 89175.7
Colours	see colour table

SPECIFICATION TEXT

Floorstanding WC pan washdown LAUFEN PRO N, sanitary ceramic,
with cistern Dual-Flush (4,5/3-l-flush)
EN 997, 4,5/3-l-flush, dimensions 360 x 650 x 890 mm
outlet vertical 70 mm
concealed fixation, 2 fixing holes
Special feature: concealed surfaces directing water are fully glazed
throughout, open water rim, vacuum checked
Further options / accessories: Surface refinement LCC, WC seat 89115.3,
WC seat and cover, 89095.0, WC seat and cover with automatic lower-
ing 89095.1
Order no. 82795.4

TECHNICAL DRAWINGS / S 1 : 20

