



## Usage:

Contact Grease Compound for aluminium conductors.

Suitable for solid class 1, stranded class 2, and special-stranded Alukaflex® conductor.

Installation of mechanical and compression cable lugs, -connectors, or -pin-connection.

Sleeves crimped on aluminium conductors when installing in CEE plugs, terminals, etc.

Tested and approved for use on aluminium cables from DanCables.

## Contents:

Oxidation-inhibiting contact grease for lubricating aluminiums conductors.

25 grams of grease are supplied in a plastic jar with a lid and an accompanying brush for application.

400 grams are supplied in a tube that requires a suitable grease gun for use.

## Installation Instructions:

Must be installed by trained personnel.

Immediately before the installation brush conductor to remove the oxide layer on the aluminium.

Lubricate the conductor with contact grease. Avoid skin contact.

Attach sleeve or compressing material to the conductor.

Ensure all strands in class 2 and special-stranded Alukaflex® are intact before crimping.

Use a crimping tool or compressing tool suitable for the cable                      mm<sup>2</sup> and material used.

For sleeves connections, the sleeve must remain intact so that the metal is not damaged or penetrated by the screw/terminal.

The use of the compressing tool depends on the manufacturer, and their instructions must be followed.

Safety datasheet available upon request.

Installation instructions for the entire DanCables power cable product range can be requested.

## Product List:

Part No.	EAN	Product Name
36050116	5714969021888	Alukaflex contact grease 25g - jar
36050115	5714969017560	Alukaflex contact grease 400g f. gun