

KA1543R-PB-UL



Item number	7298-030102
EAN	7393487036352
Pieces per pack	100
Gross weight (kg)	0.001
Depth [TrPack] (mm)	180
Width [TrPack] (mm)	87
Height [TrPack] (mm)	145

Name	KA1543R-PB-UL
Brand	ABIKO
ETIM-class	Solderless copper terminals for copper conductors (EC001052)
Country of origin	CN
Customs statistical number (taric code)	85369010 - Connections < 1000 V
Basic UOM	PCS
Net weight (kg)	0.0007
Surface protection	Tin plated
Flange shape	Ring shape
AWG-range, Min	22
AWG-range, Max	16
Nominal cross section, Min (mm ²)	0.5
Nominal cross section, Max (mm ²)	1.5
According to DIN	No
mm ² Cu	0,5-1,5
W (mm)	8
d (mm)	4.1
L1 (mm)	17.8
L (mm)	21.8
t (mm) - palm thickness	0.75
s (mm) - strip length	7
Insulation material	PA
Insulation colour	Red (insulated terminals)
Easy-entry	Yes
Screw	M4
Weight (kg)	0.0007

KA1565R-PB-UL



Item number	7298-030302
EAN	7393487036390
Pieces per pack	100
Gross weight (kg)	0.001
Depth [TrPack] (mm)	180
Width [TrPack] (mm)	87
Height [TrPack] (mm)	145

Name	KA1565R-PB-UL
Brand	ABIKO
ETIM-class	Solderless copper terminals for copper conductors (EC001052)
Country of origin	CH
Customs statistical number (taric code)	85369010 - Connections < 1000 V
Basic UOM	PCS
Net weight (kg)	0.001
Surface protection	Tin plated
Flange shape	Ring shape
AWG-range, Min	22
AWG-range, Max	16
Nominal cross section, Min (mm ²)	0.5
Nominal cross section, Max (mm ²)	1.5
According to DIN	No
mm ² Cu	0,5-1,5
W (mm)	11.6
d (mm)	4.1
L1 (mm)	21.7
L (mm)	27.5
t (mm) - palm thickness	0.75
s (mm) - strip length	7
Insulation material	PA
Insulation colour	Red (insulated terminals)
Easy-entry	Yes
Screw	M6
Weight (kg)	0.001

KA2565R-PB-UL



Item number	7298-030802
EAN	7393487036475
Pieces per pack	50
Gross weight (kg)	0.001
Depth [TrPack] (mm)	181
Width [TrPack] (mm)	87
Height [TrPack] (mm)	145

Name	KA2565R-PB-UL
Brand	ABIKO
ETIM-class	Solderless copper terminals for copper conductors (EC001052)
Country of origin	CN
Customs statistical number (taric code)	85369010 - Connections < 1000 V
Basic UOM	PCS
Net weight (kg)	0.0012
Surface protection	Tin plated
Flange shape	Ring shape
AWG-range, Min	16
AWG-range, Max	14
Nominal cross section, Min (mm ²)	1.5
Nominal cross section, Max (mm ²)	2.5
According to DIN	No
mm ² Cu	1,5-2,5
W (mm)	12
d (mm)	4.5
L1 (mm)	22
L (mm)	28
t (mm) - palm thickness	0.8
s (mm) - strip length	8
Insulation material	PA
Insulation colour	Blue (insulated terminals)
Easy-entry	Yes
Screw	M6
Weight (kg)	0.0012

KA10-18ETW



Item number	7298-011700
EAN	7393487029224
Pieces per pack	100
Gross weight (kg)	0.001
Name	KA10-18ETW
Brand	ABIKO
ETIM-class	Round or flat plug/receptacle (EC000516)
Country of origin	DE
Customs statistical number (taric code)	85369010 - Connections < 1000 V
Basic UOM	PCS
Net weight (kg)	0.0007
mm ² Cu	10
d (mm)	7.5
L1 (mm)	18
L (mm)	27
s (mm) - strip length	20
Working temperature, Min (°C)	-5
Working temperature, Max (°C)	105
Insulation colour	Ivory (end sleeves)
Weight (kg)	0.0007