

GWS 24-230 PZ

Internal ID	#57374
Master-Order-No.	0 601 8C3 400
Unit	Trade / Industry
Type	Angle, concrete grinder (electric)



Description

Product category subdivision	Angle Grinder
Positioning	Powerful and protective: 230-mm angle grinder with advanced dust protection system
Long version part 1	The powerful GWS 24-230 PZ Professional angle grinder comes with the revolutionary CYCLON TECH dust protection system and safety features for increased user protection. A tough 2,400 W motor delivers robust cutting and grinding. The built-in CYCLON TECH dust protection system prolongs lifespan by collecting up to 90% of dust into the angle grinder. Worker comfort and user protection are improved by a smoother motor operation and an anti-vibration auxiliary handle.
Long version part 2	This angle grinder is ideal for cutting metal, grinding stone, and for application on a variety of materials. It is compatible with Bosch's GDE 230 FC-S dust attachment.
Long version part 3	The GWS 24-230 PZ Professional offers a PROtection switch for enhanced user protection.
User benefit incl. Reason to believe	<ul style="list-style-type: none">• Powerful 2,400 W motor for strong cutting and grinding• Revolutionary CYCLON TECH dust protection system for significantly longer lifetime• Reduced vibration through smoother motor operation and anti-vibration auxiliary handle
Short version additional information	PROtection switch for enhanced user protection

Noise/vibration information

Noise level

The A-rated noise level of the power tool is typically as follows: Sound pressure level dB(A); Sound power level dB(A). Uncertainty K= dB.

GWS 24-230 PZ

Order No.	0 601 8C3 400
EAN-Code	4059952614625
Product Name	GWS 24-230 PZ
Title	Angle Grinder GWS 24-230 PZ Professional
Scope of supply	<ul style="list-style-type: none">• Cardboard box• Protective cover (1 619 P15 668)• Auxiliary handle (1 602 025 030)• Two-hole spanner (1 607 950 061)• Backing flange (spare part number 2 605 703 014)• Locking nut (1 603 345 043)
Short name - Scope of supply	in cardboard box with auxiliary handle
SOL Date	01.01.2022
HD SKU	☑
Packaging dimensions (width x length x height) [mm]	167 x 550 x 139
Vibration Control auxiliary handle	☑
Rated input power [W]	2400
No-load speed [rpm]	6.500
Grinding spindle thread	M14
Main handle	Barrel
Disc diameter [mm]	230
Rubber backing pad, diameter [mm]	180
Grinding head, diameter [mm]	140
Tool dimensions (width) [mm]	110

CSO selection 1

Tool dimensions (length) [mm]	530
Tool dimensions (height) [mm]	150
Weight [kg]	5,9
Switch	PROtection Switch
Noise level	The A-rated noise level of the power tool is typically as follows: Sound pressure level 104 dB(A); Sound power level 94 dB(A). Uncertainty K= 3 dB.
Product category subdivision	Angle Grinder