



S+P socket cap screws EN ISO 14579 TX

Socket cap screws with driving feature

Material: austenitic stainless steel A2

NEW
TX socket cap screws

- ▶ M 2 - length 3 - 20 mm
- ▶ M 2.5 - length 3 - 20 mm
- ▶ M 3 - length 4 - 30 mm
- ▶ M 4 - length 5 - 60 mm
- ▶ M 5 - length 6 - 60 mm
- ▶ M 6 - length 6 - 60 mm
- ▶ M 8 - length 16 - 60 mm



- ▶ S+P socket cap screws with driving feature EN ISO 14579 available in all diameters with TX drive, stainless steel A2

- ▶ The TX driving feature allows the screws to be inserted safely and easily, with no wobbling or tendency to come out.

S+P socket cap screws EN ISO 14579 TX

Socket cap screws with driving feature

Material: austenitic stainless steel A2

BENEFITS:

Wobble-free drive- The TX driving feature allows you to insert the screws safely and easily without any risk of them coming out again.

Stainless steel A2 - Austenitic stainless steel for extended periods of outdoor use

USE:

For screw connections in machine construction, the furniture industry, sanitary construction and heating construction

Use in damp rooms and outdoor applications without significant levels of chlorides or sulphur dioxides

Item data				
Nominal diameter, metric M	Total length	Thread length	ISO 14579 TX A2	Unit
2	3	3	1457922 3	500
	4	4	1457922 4	500
	5	5	1457922 5	500
	6	6	1457922 6	500
	8	8	1457922 8	500
	10	10	1457922 10	500
	12	12	1457922 12	500
	14	14	1457922 14	500
	16	16	1457922 16	500
	18	16	1457922 18	500
2,5	3	3	14579225 3	500
	4	4	14579225 4	500
	5	5	14579225 5	500
	6	6	14579225 6	500
	8	8	14579225 8	500
	10	10	14579225 10	500
	12	12	14579225 12	500
	14	14	14579225 14	500
	16	16	14579225 16	500
	18	17	14579225 18	500
3	4	4	1457923 4	1.000
	5	5	1457923 5	1.000
	6	6	1457923 6	1.000
	8	8	1457923 8	1.000
	10	10	1457923 10	1.000
	12	12	1457923 12	1.000
	14	14	1457923 14	1.000
	16	16	1457923 16	1.000
	18	18	1457923 18	1.000
	20	18	1457923 20	1.000
4	5	5	1457924 5	1.000
	6	6	1457924 6	1.000
	8	8	1457924 8	1.000
	10	10	1457924 10	1.000
	12	12	1457924 12	1.000
	14	14	1458024 14	1.000
	16	16	1457924 16	1.000
	18	18	1457924 18	1.000
	20	20	1457924 20	500
	22	20	1457924 22	500
	25	20	1457924 25	500
	30	20	1457924 30	500
	35	20	1457924 35	200
	40	20	1457924 40	200
	45	20	1457924 45	200
	50	20	1457924 50	200
	60	20	1457924 60	100

Item data				
Nominal diameter, metric M	Total length	Thread length	ISO 14579 TX A2	Unit
5	6	6	1457925 6	500
	8	8	1457925 8	500
	10	10	1457925 10	500
	12	12	1457925 12	500
	14	14	1457925 14	500
	16	16	1457925 16	500
	18	18	1457925 18	500
	20	20	1457925 20	500
	22	22	1457925 22	500
	25	22	1457925 25	200
6	30	22	1457925 30	200
	35	22	1457925 35	200
	40	22	1457925 40	200
	45	22	1457925 45	200
	50	22	1457925 50	200
	60	22	1457925 60	100
	6	6	1457926 6	500
	8	8	1457926 8	500
	10	10	1457926 10	500
	12	12	1457926 12	500
8	14	14	1457926 14	200
	16	16	1457926 16	200
	18	18	1457926 18	200
	20	20	1457926 20	200
	22	22	1457926 22	200
	25	24	1457926 25	200
	30	24	1457926 30	200
	35	24	1457926 35	200
	40	24	1457926 40	200
	45	24	1457926 45	100
8	50	24	1457926 50	100
	60	24	1457926 60	100
	16	16	1457928 16	200
	18	18	1457928 18	200
	20	20	1457928 20	200
	22	22	1457928 22	200
	25	25	1457928 25	100
	30	28	1457928 30	100
	35	28	1457928 35	100
	40	28	1457928 40	100
45	28	1457928 45	100	
	50	28	1457928 50	100
60	28	1457928 60	100	

Technical data							
ISO 14579 TX							
Ø		M 2	M 2.5	M 3	M 4	M 5	M 8
TX		6	8	10	20	25	40
dk	max.	3,80	4,50	5,50	7,00	8,50	13,00
k	max.	2,00	2,50	3,00	4,00	5,00	8,00



Schäfer + Peters GmbH
 Zeilbaumweg 32
 DE-74613 Öhringen
 Tel. +49 (0) 7941 6094-0
 Fax +49 (0) 7941 6094-700
 info@schaefer-peters.com
 www.schaefer-peters.com