

PLAST

SIDE 31 · AFSNIT 2 · 01.02.09

STILLESKRUER TYPE K

med fast base og el.forzinket skrue.

Materiale: Polyethylen, sort. Max. belastning ca. 250 kg.

VARENUMMER	BASE Ø DIAMETER MM	BASEHØJDE MM	GEVIND MM X LÆNGDE MM	PAKKEENHED
K 20 06 15	20.0	7.0	M6x13.5	100
K 20 06 20	20.0	7.0	M6x17.5	500
K 20 08 20	20.0	7.0	M8x18	100
K 20 10 20	20.0	7.0	M10x16	500
K 24 06 15	24.0	8.0	M6x13.5	500
K 24 06 20	24.0	8.0	M6x17.5	500
K 24 06 30	24.0	8.0	M6x27.5	500
K 24 08 20	24.0	8.0	M8x16	100
K 24 08 30	24.0	8.0	M8x26	100
K 24 08 40	24.0	8.0	M8x36.5	100
K 24 08 50	24.0	8.0	M8x46.5	500
K 24 10 20	24.0	8.0	M10x17	100
K 24 10 30	24.0	8.0	M10x26	100
K 24 10 40	24.0	8.0	M10x36	100
K 24 10 50	24.0	8.0	M10x46	100
K 34 08 20	34.0	9.0	M8x16.5	500
K 34 08 30	34.0	9.0	M8x25.5	100
K 34 08 40	34.0	9.0	M8x35.5	100
K 34 08 50	34.0	9.0	M8x46.5	100
K 34 10 20	34.0	9.0	M10x17.5	500
K 34 10 30	34.0	9.0	M10x25.5	100
K 34 10 40	34.0	9.0	M10x35.5	100
K 34 10 50	34.0	9.0	M10x46	100



Type K 24



Type K 34



GOTTFRED PETERSEN A/S

Ikke alle varer er
nødvendigtvis lagervarer!