

# Declaration of Performance

according to Annex III of the Regulation (EU) No. 305/2011  
(Construction Products Regulation)

## Mulcol® Multimastic SP

No. DoP-PSS-SP

**1. Unique identification code of the product-type:**

Mulcol® Multimastic SP, Firestopping Mastic

**2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):**

See batch number on the packaging of the product.

**3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

3.1 The intended use of system Mulcol® Multimastic SP is to reinstate the fire resistance performance of flexible wall, rigid wall and rigid floor constructions where they are penetrated by various services, as included in ETA 23/0060 and to reinstate the fire resistance performance of gaps and joints in and between walls and floors, as included in ETA 23/0052.

3.2 The conditions under which the system Mulcol® Multimastic SP can be used are intended for indoor use, conditions: relative humidity lower than 85% RH, excluding temperatures below 0 °C, and without exposure to rain or UV (TR 024, model Z<sub>2</sub>).

3.3 The assumed working life for Mulcol® Multimastic SP for internal conditions without exposed to UV or moisture is 25 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

**4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):**

Mulcol International  
Promenade 75  
5401 GM Uden  
The Netherlands

**5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**

Not applicable

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**

AVCP-System 1

**7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:**

Not applicable

**8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**

This Declaration of Performance has been prepared in accordance with the guidelines set out within EAD 350454-00-1104. ETA 32/0052 and ETA 23/0060 are prepared by UL International B.V. notified body 2821, Certificate of Constancy of Performance 2821-CPR-0254.

**9. Declared performance:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 13501-1
Resistance to fire	ETA 32/0052 & ETA 23/0060	EN 13501-2
Air permeability	<i>NPD</i>	EN 1026
Water permeability	<i>NPD</i>	EAD 350454-00-1104, Annex C
Release of dangerous substances	IA1, S/W2	EAD 350454-00-1104
Mechanical resistance and stability	<i>NPD</i>	EOTA TR 001
Resistance to impact/movement	<i>NPD</i>	EOTA TR 001
Adhesion	<i>NPD</i>	EOTA TR 001
Airborne sound insulation	$R_{s,w} (C;C_{tr}) = 58 (-5 ; -13)$ dB. Tested 12 mm deep with 15 mm backing	EN 10140-2
Impact sound insulation	<i>NPD</i>	EN 10140-3
Thermal properties	<i>NPD</i>	EN 12664, EN 12667, EN 12939, EN ISO 8990, EN ISO 6946, EN ISO 14683, EN ISO 10211, EN ISO 10456
Water vapour permeability	<i>NPD</i>	EN ISO 12572, EN 12086, EN ISO 10456
Durability and serviceability	Z <sub>2</sub>	EOTA TR 024

*NPD: No performance determined*

**10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed on the behalf of the manufacturer by:

Ing. W. Scheffer-Geuze  
Technical Director