

Standard: EN 50200 (PH90), IEC 61034, IEC 60331, IEC 60332-3, IEC 60332-2

Standard: EN 50200 (PH90), IEC 61034, IEC 60331, IEC 60332-3, IEC 60332-2



### Konstruktion:

#### Construction:

- |   |   |
|---|---|
| <p>1 Massiv kobberleder, entrådet kl. 1<br/>Copper conductor, solid cl. 1</p> <p>2 Brandsikkert, halogenfri silikone isolation<br/>Fire resistant halogen-free insulation</p> | <p>3 Udvendig kappe: Brandsikkert, halogenfri<br/>Outer sheath: Fire resistant, Low Smoke<br/>Zero Halogen (LSZH)</p> |
|---|---|

### Anvendelse:

#### Application:

Et brandsikkert halogenfrit kabel, der er særligt velegnet til brug i alle typer bygninger, hvor der kan være behov for ABA-anlæg, nød- og panikbelysning. Kablet skal beskyttes mod direkte UV-lys.

Fire resistant cable particularly suitable for use in all types of buildings where Fire Alarm Systems, emergency- and panic lighting may be required. The cable shall be protect from direct UV light.

### Egenskaber:

#### Properties:









Mærkespænding Rated voltage	100V	Minimum bøjeradius Min. bending radius	6 x kabel diameter 6 x cable diameter
Maximal ledertemperatur Max. conductor temperature	+90°C	CE-overensstemmelse CE-conformity	Lavspændingsdirektivet Low Voltage Directive
Drifttemperatur Operating temperature	0°C - +70°C	RoHS Fulfills RoHS	Ja Yes
Håndteringsemperatur Handling temperature	0°C - +70°C	REACH Fulfills REACH	Ja Yes

**Lederidentifikation:****Core identification:**

2-leder: Blå, mørkegrå

2-cores: Blue, dark grey

**Tekniske data:****Technical data:**

<b>Antal ledere og dimension</b> No. of cores and cross-section No. of cores and cross-section  (mm <sup>2</sup> )	<b>Levering</b> Packaging	<b>Isolation, nom.</b> Insulation, nom. dia.  (mm)	<b>Diameter, nom.</b> Diameter, nom.  (mm)	<b>Ca. vægt</b> Weight  (kg/km)	<b>Lederresistans</b> Conductor resistance  (Ω/km)	<b>EI-nummer</b> Product number	<b>EAN- nr.</b> EAN-no.
1x2x1 Rød/Red	Bobin 100	0,8	6,3	47	18,1	3033202555	
1x2x1 Rød/Red	Bobin 500	0,8	6,3	47	18,1	3033202610	
1x2x1 Rød/Red	Qaddy 500	0,8	6,3	47	18,1	3033202678	
1x2x1 Rød/Red	Qaddy 1000	0,8	6,3	47	18,1	3033202733	
1x2x1 Hvid/White	Bobin 100	0,8	6,3	47	18,1	3033202791	
1x2x1 Hvid/White	Bobin 500	0,8	6,3	47	18,1	3033202856	
1x2x1 Hvid/White	Qaddy 500	0,8	6,3	47	18,1	3033202911	
1x2x1 Hvid/White	Qaddy 1000	0,8	6,3	47	18,1	3033202979	

NKT® er et registreret varemærke ejet af NKT. Ophavsretten i dette dokument tilhører NKT på tidspunktet for udgivelse. Informationen i dokumentet er alene informativ og indeholder således ingen bindende forpligtelser eller erklæringer og ingen garantier.

NKT® is a registered trademark of NKT. © The copyright of this document is vested in NKT. All rights reserved at the time of issuance. This data was prepared for informational purposes only and does not contain any representations, legally binding declarations or guarantees.