

GO-SLIM

Flood light 10W-100W available

Thinner than thinner



Model	GD-F023T-SMT	GD-F027T-SMT	GD-F028T-SMT
Power	10W	20W	30W
LED Luminous Flux	1000lm	2000lm	3000lm
	3000K-3500K	3000K-3500K	3000K-3500K
Color Temperature	4000K-4500K	4000K-4500K	4000K-4500K
	5500K-6000K	5500K-6000K	5500K-6000K
Color Rendering Index	Ra>70	Ra>70	Ra>70
Humidity	0-90%	0-90%	0-90%
Housing Material	Aluminum & Iron	Aluminum & Iron	Aluminum & Iron
Operating Temperature	-20°C to 55°C	-20°C to 55°C	-20°C to 55°C
Input Voltage	Input 220-240V AC	Input 220-240V AC	Input 220-240V AC
Beam angle	120°	120°	120°
Operating temperature	-20°C to 55°C	-20°C to 55°C	-20°C to 55°C
Dimension	102.7x82.7x24 mm	159.2x 121.7x26 mm	205.5x 160x 33.5 mm



Model	GD-F050T-SMT	GD-F100T-SMT	GD-F200-T-SMT
Power	50W	100W	200W
LED Luminous Flux	5000lm	10000lm	20000lm
	3000K-3500K	3000K-3500K	3000K-3500K
Color Temperature	4000K-4500K	4000K-4500K	4000K-4500K
	5500K-6000K	5500K-6000K	5500K-6000K
Color Rendering Index	Ra>70	Ra>70	Ra>70
Humidity	0-90%	0-90%	0-90%
Housing Material	Aluminum & Iron	Aluminum & Iron	Aluminum & Iron
Operating Temperature	-20°C to 55°C	-20°C to 55°C	-20°C to 55°C
Input Voltage	Input 220-240V AC	Input 220-240V AC	Input 220-240V AC
Beam angle	120°	120°	120°
Operating temperature	-20°C to 55°C	-20°C to 55°C	-20°C to 55°C
Dimension	270x 209x 33.5mm	380 x 280x 43.5 mm	445x 335x45 mm

