

TECHNICAL DATA SHEET



PRODUCT NAME

blackbolt® Universal Grease (NSF)

PRODUCT NUMBER

3356985016

PRODUCT DESCRIPTION

Universal Grease is a white grease, which has been specially developed to meet the highest requirements for lubrication of equipment in the food industry. Used as a lubricant on conveyor belts, skids, pipes, cable runs, etc. Withstands being washed away by water and cleaning with most chemicals. Withstands extreme pressure, counteracts wear while protecting against corrosion at the same time. Prevents damage to bearings and gears caused by damp/water. Does not stain clothing, wood or porous materials. The product acts well in connection with HACCP and GMP approval.

PROPERTIES

Universal lubricant
Withstands being washed away with water
Aluminium Complex EP-2 grease

DIRECTIONS FOR USE

Shake the container and spray directly on to the article. Operating temperature range -40°C to +180°C.

MARKINGS/SAFETY

Extremely flammable aerosol. Pressurised container: May burst if heated. If medical advice is needed, have product container or label at hand. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. **Keep out of reach of children.**



Danger!

PR number	2114619
Net	345 g.
Volumen	500 ml.
Propellant	Carbon dioxide

Shelf life	Three years from date of manufacture. The product can be used for up to six years after the date of production, provided there is sufficient spray pressure to allow it to be applied to the surface in a satisfactory manner.
------------	--