


ISO 4028 A4  
Gewindestifte mit Innensechskant und Zapfen

ISO 4028 A4  
Hexagon socket set screws with dog point

ISO 4028  
A4

Alternative Norm  
ehemals DIN 915

d	M 2	M 2,5	M 3	M 4	M 5	M 6
<b>l/mm</b>	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.	Art. Nr. / Item no.
2	402842 2					
3	402842 3	4028425 3	402843 3	402844 3		
4	402842 4	4028425 4	402843 4	402844 4	402845 4	
5	402842 5	4028425 5	402843 5	402844 5	402845 5	402846 5
6	402842 6	4028425 6	402843 6	402844 6	402845 6	402846 6
8	402842 8	4028425 8	402843 8	402844 8	402845 8	402846 8
10	402842 10	4028425 10	402843 10	402844 10	402845 10	402846 10
12	402842 12	4028425 12	402843 12	402844 12	402845 12	402846 12
14	402842 14	4028425 14	402843 14	402844 14	402845 14	402846 14
16	402842 16	4028425 16	402843 16	402844 16	402845 16	402846 16
18			402843 18	402844 18	402845 18	402846 18
20			402843 20	402844 20	402845 20	402846 20
25			402843 25	402844 25	402845 25	402846 25
30			402843 30	402844 30	402845 30	402846 30
35			402843 35	402844 35	402845 35	402846 35
40			402843 40	402844 40	402845 40	402846 40
45				402844 45	402845 45	402846 45
50				402844 50	402845 50	402846 50
55					402845 55	402846 55
60					402845 60	402846 60
70						402846 70
80						402846 80
90						
100						
120						



z = nach DIN,  
Längenabhängig

z = acc. to DIN, dependent  
on length

	500	500	500 ≥ 30 200	500 ≥ 30 200	500 ≥ 25 200	200
<b>z</b>	0,5	0,63	0,75	1	1,25	1,5
	1	1,25	1,5	2	2,5	3
<b>dp</b>	0,75	1,25	1,25	1,75	3,2	3,7
<b>Antrieb</b>	SW 0,9	SW 1,3	SW 1,5	SW 2	SW 2,5	SW 3

ISO