

Overall Datasheet for K3000 Series

Hele serien er forsikret med 16A, men kommer på lager med forskellige termorelæ'er.

Fra 3,0A op til 16,0A.

Series Specifications

Startup	Direct startup
Rated operating voltage Ue	400V/50Hz
Rated operating current Ie	16A
Connection	3-phase 400V
Type of actuation	Push buttons On/Off
Keypad	with protective cap
Installation position	Arbitrary, except keyboard upwards.
Mounting dimension	68×68mm or with mounting tabs
Switching functions	0-1
Pre-insurance	16A gL/gG
Ambient temperature	-10°C...+40°C
Enclosure material	ABS gray or yellow
Impact resistance	IK08
Material collar plug	PA6 red
Degree of protection	IP54
Conformity	CE

Individual Parameters

Network input	CEE collar plug 3P+N+E 16A 400V with phase converter
Motor connection	1m H07RN-F 4G1.5
Undervoltage release Uc	400V/50Hz
electronic brake	Yes
Maximum braking current	16 A
Circuit for mechanical brake	No
Overload protection	Yes
Setting overload protection	1...16A, fixed setting - Please specify motor rated current at the end of the ordering process.
Emergency stop	Yes
Rotary field detection	No
Pole switch	No
Limit switch connection possible	No
Actuation	electric on/mechanical off
Fastening	68×68mm
Mounting tabs	No
switching frequency	20/h at 10A braking current
degree of protection	IP54
Weight	0.775 kg

