



Dome-Top® BT1M-C0 Barb Tie, Black, UV PA6.6, 4"L, 18lb, PK100

BT1M-C0

The BT1M-C0 Dome-Top® barb tie, features a unique patented design with its round smooth edges. Paired with the stainless-steel locking barb, these cable ties provide consistent performance, reliability and infinite adjustability through the entire bundle range. Miniature cross section, 4.0" (102mm) length. Appropriate for Indoor/Outdoor use, made of Weather Resistant Nylon 6.6 with high resistance to ultraviolet light, are black in color and come in packages of 100.

Specifications

Material Description	Nylon 6.6 (UV-Resistant, Weather-Resistant)
Product Type	Cable Tie
Sub Brand	Dome-Top®
Color	Black
Environment	Indoor/Outdoor
Material	Nylon 6.6
Resistance Properties	UV-Resistant, Weather-Resistant
Overall Length (In.)	4
Overall Length (mm)	102
Body Width (In.)	0.095
Body Width (mm)	2.4
Body Thickness (In.)	0.036
Body Thickness (mm)	0.9
Maximum Bundle Diameter (In.)	0.9
Maximum Bundle Diameter (mm)	23
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Loop Tensile Strength (N)	80
Minimum Loop Tensile Strength (lb)	18
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4

Specifications (continued)

Standards Met	UL 62275 (File E56854), CSA-C22.2 No. 62275, 11130200, NRC 10CFR50, QPL-AS23190, CSA Certified, RoHS Compliant
For Use With	GTS-E, GS2B-E, PTS, PPTS, STS2

Packaging Detail

UPC	07498341303
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0237
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.2370