



PLT2S-C10 Premium Cable Tie

PLT2S-C10

Pan-Ty® locking tie, standard cross section, 7.4 (188mm) length, nylon 6.6, white, standard package.

Specifications

Product Type	Premium Cable Tie
Color	White
Environment	Plenum
Material	Nylon 6.6
Overall Length (In.)	7.4
Overall Length (mm)	188
Body Width (In.)	0.19
Body Width (mm)	4.8
Body Thickness (In.)	0.052
Body Thickness (mm)	1.3
Maximum Bundle Diameter (In.)	1.88
Maximum Bundle Diameter (mm)	47.8
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Loop Tensile Strength (N)	222
Minimum Loop Tensile Strength (lb)	50
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant (Type 2, 21), RoHS Compliant
For Use With	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH
Application	General
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.

Packaging Detail

UPC	07498354766
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0321
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.3207