



## **Pan-Ty® PLT4S-C4Y Cable Tie, Yellow, PA6.6, 14.5"L, 50lb, PK100**

PLT4S-C4Y

Panduit PLT4S-C4Y Locking Cable Ties are designed to satisfy the needs of mil spec applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Standard cross section, 14.5" (368mm) length. Made of Nylon 6.6, are yellow in color and come in packages of 100.

### **Specifications**

Product Type	Premium Cable Tie
Color	Yellow
Environment	Indoor
Material	Nylon 6.6
Overall Length (In.)	14.5
Overall Length (mm)	368
Body Width (In.)	0.19
Body Width (mm)	4.8
Body Thickness (In.)	0.052
Body Thickness (mm)	1.3
Maximum Bundle Diameter (In.)	4
Maximum Bundle Diameter (mm)	102
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Loop Tensile Strength (N)	222
Minimum Loop Tensile Strength (lb)	50
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant (Type 2S, 21S), RoHS Compliant
Military Cross Reference Number	MS3367-2-4
For Use With	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2

**Specifications (continued)**

Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.
---------------	--

**Packaging Detail**

UPC	07498344435
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0556
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.5563