



Pan-Ty® PLT5H-C0 Cable Tie, Black, UV PA6.6, 17.7"L, 175lb, PK100

PLT5H-C0

Panduit PLT5H-C0 Locking Cable Ties are designed to satisfy the needs of general applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Heavy cross section, 17.7" (450mm) length. For Indoor/Outdoor use, made of Weather Resistant Nylon 6.6, are black in color and come in packages of 100.

Specifications

Product Type	Premium Cable Tie
Color	Black
Environment	Indoor/Outdoor
Material	Nylon 6.6
Resistance Properties	UV-Resistant, Weather-Resistant
Overall Length (In.)	17.7
Overall Length (mm)	450
Body Width (In.)	0.35
Body Width (mm)	8.9
Body Thickness (In.)	0.078
Body Thickness (mm)	2
Maximum Bundle Diameter (In.)	5
Maximum Bundle Diameter (mm)	127
Minimum Bundle Diameter (In.)	0.188
Minimum Bundle Diameter (mm)	4.8
Minimum Loop Tensile Strength (N)	778
Minimum Loop Tensile Strength (lb)	175
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant (Type 1, 11), RoHS Compliant
For Use With	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH

Specifications (continued)

Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.
---------------	--

Packaging Detail

UPC	07498338774
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.1082
Std. Ctn. Qty.	2000
Std. Ctn. Volume (cf)	2.1638