



## PLT6H-L0 Premium Cable Tie

### PLT6H-L0

Panduit PLT6H-L0 Locking Cable Ties are designed to satisfy the needs of weather resistant applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Heavy cross section, 20.9" (530mm) length. Made of Weather Resistant Nylon 6.6, are black in color and come in packages of 50.

### Specifications

Product Type	Premium Cable Tie
Color	Black
Environment	Indoor/Outdoor
Material	Nylon 6.6
Resistance Properties	UV-Resistant, Weather-Resistant
Overall Length (In.)	20.9
Overall Length (mm)	530
Body Width (In.)	0.35
Body Width (mm)	8.9
Body Thickness (In.)	0.078
Body Thickness (mm)	2
Maximum Bundle Diameter (In.)	6
Maximum Bundle Diameter (mm)	152
Minimum Bundle Diameter (In.)	0.188
Minimum Bundle Diameter (mm)	4.8
Minimum Loop Tensile Strength (N)	778
Minimum Loop Tensile Strength (lb)	175
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant (Type 1, 11), RoHS Compliant
For Use With	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.

**Packaging Detail**

UPC	07498354107
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.1174
Std. Ctn. Qty.	500
Std. Ctn. Volume (cf)	1.1740