



## **Pan-Ty® PLT8LH-C0 Cable Tie, Black, UV PA6.6, 27.6"L, 120lb, PK100**

PLT8LH-C0

Panduit PLT8LH-C0 Locking Cable Ties are designed to satisfy the needs of weather resistant applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Light-Heavy cross section, 27.6" (701mm) length. Made of Weather Resistant Nylon 6.6 with high resistance to ultraviolet light, are black in color and come in packages of 100.

### Specifications

Product Type	Premium Cable Tie
Color	Black
Environment	Indoor/Outdoor
Material	Nylon 6.6
Resistance Properties	UV-Resistant, Weather-Resistant
Overall Length (In.)	27.6
Overall Length (mm)	701
Body Width (In.)	0.3
Body Width (mm)	7.6
Body Thickness (In.)	0.075
Body Thickness (mm)	1.9
Maximum Bundle Diameter (In.)	8
Maximum Bundle Diameter (mm)	203
Minimum Bundle Diameter (In.)	0.188
Minimum Bundle Diameter (mm)	4.8
Minimum Loop Tensile Strength (N)	534
Minimum Loop Tensile Strength (lb)	120
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	CSA Certified, RoHS Compliant
For Use With	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.

**Packaging Detail**

UPC	07498338350
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0732
Std. Ctn. Qty.	2000
Std. Ctn. Volume (cf)	1.4644