



Pan-Ty® PLT9LH-C0 Cable Tie, Black, UV PA6.6, 30.5"L, 120lb, PK100

PLT9LH-C0

Panduit PLT9LH-C0 Locking Cable Ties are designed to satisfy the needs of general applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Light-heavy cross section, 30.5" (775mm) length. For Indoor/Outdoor use, made of Weather Resistant Nylon 6.6, are black in color and come in packages of 100.

Specifications

Product Type	Premium Cable Tie
Color	Black
Environment	Indoor/Outdoor
Material	Nylon 6.6
Resistance Properties	UV-Resistant, Weather-Resistant
Overall Length (In.)	30.5
Overall Length (mm)	775
Body Width (In.)	0.3
Body Width (mm)	7.6
Body Thickness (In.)	0.075
Body Thickness (mm)	1.9
Maximum Bundle Diameter (In.)	9
Maximum Bundle Diameter (mm)	229
Minimum Bundle Diameter (In.)	0.188
Minimum Bundle Diameter (mm)	4.8
Minimum Loop Tensile Strength (N)	534
Minimum Loop Tensile Strength (lb)	120
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	CSA Certified, RoHS Compliant
For Use With	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.

Packaging Detail

UPC	07498354179
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.1453
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	1.4527