

PM1303 - Paper Masking Tape

Description	This single sided tape consists of a crepe paper carrier and a solvent based natural rubber adhesive.
Product properties	It has good adhesion, is conformable, and has good temperature resistance. It is compatible with most common paints and thinners, it is easy to remove without breaking, and it is hand tearable. Can be used with drying cycles from infrared lamps. It should not be exposed to sunlight, and should be removed shortly after the paint has dried.
Specifications	Fulfil EU-directive 2002/95/EC (RoHS).
Applications	It is used for general indoor masking during painting and spray work, also for automotive repair work. It is suitable for 80°C oven drying (short time 30 min in 110°C).
Storage and ageing	1 year shelf life whilst stored in ambient room temperatures. Keep out of direct sunlight.
Applying tips	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.

TECHNICAL DATA

Color	Yellow	
Thickness carrier	0.09 mm	3.543 Mils
Thickness total	0.135 mm	5.315 Mils
Adhesion on SS	4.5 N/25mm	1.03 Lbs/inch
Tensile strength length	87 N/25mm	19.87 Lbs/inch
Elongation length	9 %	
Service temperature	Between 0 and 80 °C	Between 32 and 176 °F
Temperature performance (short time)	110 °C	230 °F
Application temperature	minimum 15 °C	minimum 59 °F

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information. See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application. The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use. Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.

Stokvis Tapes Denmark A/S
 Gydevang 40
 3450 Allerød

+45 - 48 17 12 11
www.stokvistapes.dk
info@stokvistapes.dk
 An Illinois Tool Works Company