



PN411 - PVC plasttape

Description	Denne tape består af en folie af blødgjort pvc med en gummibaseret klæber.
Product properties	Blød PVC tape med special gummibaseret klæber, der på de fleste overflader vil kunne fjernes uden at efterlade limrester. Resistent mod olier, syrer, alkalier, saltvand og de fleste opløsningsmidler.
Specifications	Indeholder: DEHP
Applications	Kan med fordel anvendes som overflade beskyttelsestape specielt indenfor byggeindustrien.
Storage and ageing	Opbevaring ved +20°C og 50% relativ fugtighed - og ikke i direkte sol.
Applying tips	Overfladen, hvor tapen monteres, skal være ren, tør og fri for fedt og olie. Emnerne skal, så vidt muligt have samme temperatur.

TECHNICAL DATA

Carrier	PVC/film, soft	
Adhesive	Rubber synthetic	
Colour	Dark Green, Yellow	
Liner	None	
Weather resistant	Yes	
Ageing resistant	Yes	
Thickness Total	0,15 mm	5,91 Mils
Adhesion on stainless steel	3,1 N/25mm	0,708 Lbs/inch
Tensile strength length	49 N/25mm	11,2 Lbs/inch
Elongation length	200 %	
Temperature performance (short time)	80 °C	176 °F
Service temperature	Between -15 and 60 °C	Between 5 and 140 °F
Application temperature	Minimum -5 °C	Minimum 23 °F

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.

See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use.

Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.

Stokvis Tapes (UK) Ltd
Unit 8, Tring Industrial Estate
Icknield Way, Tring, Hertfordshire
tel +44 (0)14 42 82 17 00
fax +44 (0)14 42 82 17 22
www.stokvistapes.co.uk
info@stokvistapes.co.uk