

Standard: HD 21.3, HD 21

Standard: HD 21.3, HD 21

**Konstruktion:**

Construction:

- | | |
|---|---|
| 1 Kobberleder, mangetrådet kl. 5
Copper conductor, stranded, cl. 5 | 2 Blyfri PVC, varmebestandig
Un-lead PVC, heat resistant |
|---|---|

Anvendelse:

Application:

Varmebestandig monteringsledninger der anvendes som indre ledninger i brugs- og belysningsgenstande. Må kun installeres af en autoriseret elinstallatør.

Cables to be installed inside electrical devices and lighting components. Installation to be performed by a licensed electrician only.

Egenskaber:


Properties:

Mærkespænding Rated voltage	450/750 V
Prøvespænding Test voltage	2,5 kV AC
Max. drifttemperatur Max. operating temperature	90 °C
Max. ledertemperatur Max. conductor temperature	90 °C
Max. kortslutningstemperatur Max. short-circuit temperature	160 °C
Min. håndteringstemperatur Min. handling temperature	5 °C

Max. lagertemperatur Max. storage temperature	40 °C
Brandprøve Fire test	IEC 60332-1
Min. bøjeradius Min. bending radius	6 x kabeldiameter 6 x cable diameter
CE-overensstemmelse CE-conformity	Lavspændingsdirektivet Low Voltage Directive
RoHS Rohs	Ja Yes

Tekniske data (G):

Technical data (G):

Dimension No. of cores and cross-section	Levering Delivery	Farve Colour	Udvendig di- mension, nom. Outer diameter, nom.	Udvendig dimen- sion max. Outer diameter max.	Ca. vægt Cable mass approx.	El-nr. Product number	EAN-nr. EAN-nr.
mm ²	m		mm	mm	kg/km		
1X50	Rg 50	Sort/black	11,8	13,9	536	30 32 639 103	 5 702950 130510

NKT® er et registreret varemærke ejet af NKT. Ophavsretten i dette dokument tilhører NKT på tidspunktet for udgivelse. Informationen i dokumentet er alene informativ og indeholder således ingen bindende forpligtelser eller erklæringer og ingen garantier.

NKT® is a registered trademark of NKT. © The copyright of this document is vested in NKT. All rights reserved at the time of issuance. This data was prepared for informational purposes only and does not contain any representations, legally binding declarations or guarantees.