

Monteringsledninger, PVC-isolerede

Wires, PVC insulated

Standard: HD 21.3

Standard: HD 21.3



Konstruktion:

Construction:

1 Kobberleder, mangetrådet kl. 5
Copper conductor, stranded, cl. 5

2 Isolation, blyfri PVC
Insulation, lead-free PVC

Anvendelse:

Application:

Indre ledninger i brugsgenstande, belysningsgenstande m.v. i.h.t. konstruktionsforskrifterne.

For internal wiring in utility products and lighting articles according to construction directions.

Egenskaber:





















Properties:

Mærkespænding AC Rated voltage AC	300/500 V
Prøvespænding DC Test voltage DC	2 kV AC
Max. drifttemperatur Max. operating temperature	70 °C
Max. kortslutningstemperatur Max. short-circuit temperature	160 °C
Min. håndteringstemperatur Min. handling temperature	5 °C

Max. lagertemperatur Max. storage temperature	40 °C
Brandprøve Fire test	IEC 60332-1
CE-overensstemmelse CE-conformity	Lavspændingsdirektivet Low Voltage Directive
RoHS	Ja
RoHS	Yes
Certificering Certificate	HAR HAR








Tekniske data (G):

Technical data (G):

Dimension No. of cores and cross-section	Farve Color	Levering Delivery	Udvendig dimen- sion, nom. Outer diameter, nom.	Udvendig dimen- sion max. Outer diameter max.	Ca. vægt Cable mass approx.	El-nr. Product number	EAN-nr. EAN-nr.
mm ²		m	mm	mm	kg/km		
1X0,5	Hvid White	Tb 4000	2,2	2,5	9	30 32 203 623	
1X0,5	Lysegrå Light grey	Tb 4000	2,2	2,5	9	30 32 203 034	
1G0,75	Grøn/gul Green/yellow	Sp 100	2,3	2,7	12	30 32 200 082	
1G0,75	Grøn/gul Green/yellow	Tb 3000	2,3	2,7	12	30 32 713 508	
1G0,75	Grøn/gul Green/yellow	Rg 100	2,3	2,7	12	30 32 306 449	
1X0,75	Blå Blue	Sp 100	2,3	2,7	12	30 32 200 037	
1X0,75	Blå Blue	Tb 3000	2,3	2,7	12	30 32 713 430	
1X0,75	Brun Brown	Rg 100	2,3	2,7	12	30 32 306 410	
1X0,75	Brun Brown	Tb 3000	2,3	2,7	12	30 32 713 456	
1X0,75	Hvid White	Rg 100	2,3	2,7	12	30 32 306 384	
1X0,75	Lysegrå Light grey	Sp 100	2,3	2,7	12	30 32 200 066	
1X0,75	Lysegrå Light grey	Tb 3000	2,3	2,7	12	30 32 713 469	
1X0,75	Mørkeblå Dark blue	Sp 100	2,3	2,7	12	30 32 306 368	
1X0,75	Mørkegrå Dark grey	Sp 100	2,3	2,7	12	30 32 200 079	
1X0,75	Orange Orange	Sp 100	2,3	2,7	12	30 32 200 040	
1X0,75	Rød Red	Sp 100	2,3	2,7	12	30 32 306 452	
1X0,75	Rød Red	Tb 3000	2,3	2,7	12	30 32 306 135	
1X0,75	Sort Black	Sp 100	2,3	2,7	12	30 32 306 397	
1X0,75	Sort Black	Tb 3000	2,3	2,7	12	30 32 713 401	
1G1	Grøn/gul Green/yellow	Sp 100	2,5	2,8	15	30 32 306 494	
1X1	Blå Blue	Sp 100	2,5	2,8	15	30 32 306 478	

Tekniske data (G):

Technical data (G):

Dimension No. of cores and cross-section	Farve Color	Levering Delivery	Udvendig dimen- sion, nom. Outer diameter, nom.	Udvendig dimen- sion max. Outer diameter max.	Ca. vægt Cable mass approx.	El-nr. Product number	EAN-nr. EAN-nr.
mm ²		m	mm	mm	kg/km		
1X1	Brun Brown	Sp 100	2,5	2,8	15	30 32 210 056	
1X1	Hvid White	Sp 100	2,5	2,8	15	30 32 306 588	
1X1	Mørkeblå Dark blue	Sp 100	2,5	2,8	15	30 32 306 504	
1X1	Mørkegrå Dark grey	Sp 100	2,5	2,8	15	30 32 210 072	
1X1	Rød Red	Sp 100	2,5	2,8	15	30 32 306 465	
1X1	Sort Black	Sp 100	2,5	2,8	15	30 32 210 014	
1X1	Grå Grey	Tb 2500	2,5	2,8	15	30 32 714 277	

NKT® er et registreret varemærke ejet af NKT. Ophavsretten i dette dokument tilhører NKT på tidspunktet for udgivelse. Informationen i dokumentet er alene informativ og indeholder således ingen bindende forpligtelser eller erklæringer og ingen garantier.

NKT® is a registered trademark of NKT. © The copyright of this document is vested in NKT. All rights reserved at the time of issuance. This data was prepared for informational purposes only and does not contain any representations, legally binding declarations or guarantees.