Kabelverschraubung SCHLEMMER-TEC

Messing vernickelt
NPT-Gewinde

Cable gland SCHLEMMER-TEC

nickel-plated brass
NPT-thread

RoHS | IP 68



Material:
- 1/3: Verschraubungskörper/ Hutmutter: Messing vernickelt
- 2: Dichtung: Neopren

Temperaturbereich:
-40°C bis 100°C

Farbe(n)/Ausführungen:
- Außengewinde: NPT
- Reduzier-Dichteinsatz

Eigenschaften:
- optimale Zugentlastung durch Klemmlamellen
- gas- und wasserdicht

Zubehör (siehe Kapitel…):
- Gegenmuttern (3.3)
- Montagezange Mon.Za (3.1)

Anwendungsbereiche:
- Maschinen- und Anlagenbau
- Photovoltaik
- Automatisierungstechnik

Material:
- 1/3: Gland element/Cap nut: nickel-plated brass
- 2: Sealing: Neoprene

Temperature range:
-40°C to 100°C

Colour(s)/Designs:
- External thread: NPT
- reduction sealing insert

Characteristics:
- maximum strain relief through clamp lamella
- gas and water-tight

Accessories (see chapter…):
- lock nuts (3.3)
- Mounting tool Mon.Za (3.1)

Applications:
- Machine and apparatus construction
- Photovoltaic
- Automation technology

Außengewinde **External thread**	**Klemmbereich mm** **Clamping range mm**	**Gewindelänge (E) mm** **Thread length (E) mm**	**SW 1 mm** **SW 1 mm**	**SW 2 mm** **SW 2 mm**	**Art.-Nr. vernickelt** **Art. no. nickel-plated**	**VE Stck.** **PU pcs.**
NPT 3/8”	4,0 - 9,5	15,0	17,0	18,0	4220800	50
NPT 1/2”	7,0 - 13,0	20,0	22,0	23,0	4220801	50
NPT 3/4”	8,0 - 16,0	20,0	27,0	28,0	4220802	20
NPT 1”	11,0 - 21,0	25,0	34,0	36,0	4220803	20
mit Reduzier-Dichteinsatz / with reduction sealing insert						
NPT 3/8” RED	2,5 - 7,0	15,0	17,0	18,0	4220810	50
NPT 1/2” RED	4,0 - 10,0	20,0	22,0	23,0	4220811	50
NPT 3/4” RED	5,0 - 13,0	20,0	27,0	28,0	4220812	20
NPT 1” RED	7,0 - 17,0	25,0	34,0	36,0	4220813	20