

NETWORK MODULES

Discover our connectivity with our range of network hardware components. Crafted with professional materials and engineered for performance, each piece in our collection offers reliability and durability, ensuring your network stays robust and responsive. Whether you're looking for sleek silver or classic white, our components are designed to seamlessly integrate with your system. Experience the perfect blend of quality and functionality with our products and elevate your connectivity.



STATIONSALLEEN 40 • DK-2730 HERLEV

	Type nr.	Art. nr.	EAN nr.	Product Material	Color	Width mm	Length mm	Operating temp.	Bags per carton	Weight per bag (grams)
	403001	7800403001	5707157618939	Body: ABS & Chromium Plated PCB: FR-4 / UL-94V0 IDC Cap: Fireproof PC IDC Body: Fireproof ABS UL-94V0 IDC Pin: Phosphor Bronze & Tinned IDC Description: For 22-26 AWG. For 110 or Krone punch-down Tooless (when use IDC cap directly). Cat 6A. Standed and solid within the range of 22-26 AWG.	Silver	25.8	48	- 40 ~ + 70 °C	500	24.8
	403005	7800403005	5707157602839	ABS, UL 94 V-0. Can accomodate Keystone Jacks. Can be combined with multiple outlets But only of same type.	White	37.00	65.10	-10 ~ +60°C	250	33.6
	403006	7800403006	5707157602402	Housing: ABS, UL 94 V-0. Applicable for Key Stone Cutout locking height 20.05 F Adapter housing: Brass, nickel Insulator:PP resin	White	16.70	28.5	-10 ~ +60°C	1,000	8.3
	403007	7800403007	5707157602440	Housing: ABS, UL 94 V-0 Contact: Copper alloy Contact area: Copper alloy, plated with thick hard gold Shell: copper alloy. Socket hole/format: Key Stone locking height 19.2. HDMI 2.0	White	16.56	38	-10 ~ +60°C	1,000	13
	403008	7800403008	5707157602419	Housing: ABS, UL 94 V-0 Nut: Iron. Pin: Phosphor Bronze. Outlet: Key Stone Jack cut-out. Locking height 20.05.	White	16.70	36	-10 ~ +60°C	1,000	11.3
	404009	7800404009	5707157780278	Overall Shield: Brass, nickel plated Housing: ABS. Cat 6A Jack Contacts: Phosphor Bronze , plated with gold over nickel PCB: FR4 Overall Shield: Brass, nickel plated Housing: ABS. Cat 6A Jack Contacts: Phosphor Bronze , plated with gold over nickel PCB: FR4	Silver	14.60 mm	29.95 mm	-10 ~ 60°C	1,000	11
	404010	7800404010	5707157780254	Housing: PC Jack Contacts: Phosphor Bronze, plated with gold over nickel PCB: FR4	White	14.60 mm	29.60 mm	-10 ~ 60°C	1,000	8.9
	404011	7800404011	5707157780261	Housing:PC Jack Contacts: Phosphor Bronze, plated with gold over nickel PCB: FR4. Outlet: Keystone Jack cut-out locking height 20.05	White	14.60mm	29.60 mm	-10 ~ 60°C	1,000	8.9